

1 Identification

- **Product identifier**
- **Trade name:** 19353 Toyota Red Pearl 3R3
- **Article number:** 19353
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222

Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas

H280

Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2

H351

Suspected of causing cancer.

Repr. 2

H361

Suspected of damaging fertility or the unborn child.

STOT RE 1

H372-H373

Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A

H319

Causes serious eye irritation.

STOT SE 3

H336

May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 1)

· Hazard pictograms



· Signal word *Danger*

· Hazard-determining components of labeling:

acetone
toluene
4-methylpentan-2-one
n-butyl acetate

· Hazard statements

H222 *Extremely flammable aerosol.*
H280 *Contains gas under pressure; may explode if heated.*
H319 *Causes serious eye irritation.*
H351 *Suspected of causing cancer.*
H361 *Suspected of damaging fertility or the unborn child.*
H336 *May cause drowsiness or dizziness.*
H372-H373 *Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.*

· Precautionary statements

P201 *Obtain special instructions before use.*
P202 *Do not handle until all safety precautions have been read and understood.*
P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Pressurized container: Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P264 *Wash thoroughly after handling.*
P270 *Do not eat, drink or smoke when using this product.*
P271 *Use only outdoors or in a well-ventilated area.*
P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P308+P313 *IF exposed or concerned: Get medical advice/attention.*
P312 *Call a poison center/doctor if you feel unwell.*
P314 *Get medical advice/attention if you feel unwell.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
P405 *Store locked up.*
P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· Classification system:

· NFPA ratings (scale 0 - 4)



(Contd. on page 3)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

67-64-1	acetone	13-30%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
108-65-6	2-methoxy-1-methylethyl acetate	10-13%
123-86-4	n-butyl acetate	10-13%
110-19-0	isobutyl acetate	5-7%
108-88-3	toluene	1.5-5%
763-69-9	ethyl 3-ethoxypropionate	1.5-5%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	1.5-5%
108-10-1	4-methylpentan-2-one	1-1.5%
100-41-4	ethylbenzene	≥0.1-≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
123-86-4	n-butyl acetate	5 ppm
110-19-0	isobutyl acetate	450 ppm
108-88-3	toluene	67 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
108-10-1	4-methylpentan-2-one	75 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
71-36-3	butan-1-ol	60 ppm
25322-68-3	Polyethylene glycol	30 mg/m ³

· **PAC-2:**

67-64-1	acetone	3200* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
123-86-4	n-butyl acetate	200 ppm
110-19-0	isobutyl acetate	1300* ppm
108-88-3	toluene	560 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
108-10-1	4-methylpentan-2-one	500 ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
71-36-3	butan-1-ol	800 ppm
25322-68-3	Polyethylene glycol	1,300 mg/m ³

(Contd. on page 5)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 4)

· PAC-3:		
67-64-1	acetone	5700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
123-86-4	n-butyl acetate	3000* ppm
110-19-0	isobutyl acetate	7500** ppm
108-88-3	toluene	3700* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
108-10-1	4-methylpentan-2-one	3000* ppm
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppm
25322-68-3	Polyethylene glycol	7,700 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm
BEI	

(Contd. on page 6)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 5)

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Long-term value: 950 mg/m³, 200 ppm

TLV Short-term value: 712 mg/m³, 150 ppm

Long-term value: 238 mg/m³, 50 ppm

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm

Long-term value: 238 mg/m³, 50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 307 mg/m³, 75 ppm

Long-term value: 82 mg/m³, 20 ppm

BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm

BEI

Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 7)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 6)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

108-10-1 4-methylpentan-2-one

BEI 1 mg/L
Medium: urine
Time: end of shift
Parameter: MIBK

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 7)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Aerosol
· Color:	Red
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55.8-56.6 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.
Avoid high heat

· **Explosion limits:**

· Lower:	1.9 Vol %
· Upper:	13 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.75196 g/cm³

(Contd. on page 9)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 8)

· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	93.0 %
VOC content:	63.13 %
	663.2 g/l / 5.53 lb/gl
· Solids content:	7.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Nitrogen oxides
Hydrocarbons
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
108-10-1	4-methylpentan-2-one	2B
1330-20-7	xylene	3

(Contd. on page 10)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 9)

100-41-4 ethylbenzene

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1950

· **UN proper shipping name**

· **DOT**

Aerosols, flammable

· **ADR**

1950 Aerosols

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

(Contd. on page 11)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Gases

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 12)

USA



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 11)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

	Acrylic Resin
108-88-3	toluene
108-10-1	4-methylpentan-2-one
1330-20-7	xylene
100-41-4	ethylbenzene
71-36-3	butan-1-ol

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
108-65-6	2-methoxy-1-methylethyl acetate
123-86-4	n-butyl acetate
110-19-0	isobutyl acetate
108-88-3	toluene
763-69-9	ethyl 3-ethoxypropionate
9004-36-8	Cellulose Acetate Butyrate
64742-88-7	Solvent naphtha (petroleum), medium aliph.
108-10-1	4-methylpentan-2-one
110-43-0	heptan-2-one
6358-30-1	Violet Pigment
1330-20-7	xylene
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
100-41-4	ethylbenzene

(Contd. on page 13)



Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 12)

71-36-3	butan-1-ol
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
104810-48-2	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -hydroxy-
104810-47-1	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
25322-68-3	Polyethylene glycol
106-79-6	Dimethyl sebacate(Impurity)
2403-89-6	4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)

· **TSCA new (21st Century Act) (Substances not listed)**

68476-86-8 Petroleum gases, liquefied, sweetened

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1 4-methylpentan-2-one

1330-20-7 xylene

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

108-10-1 4-methylpentan-2-one

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
108-10-1	4-methylpentan-2-one	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
71-36-3	butan-1-ol	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 13)

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

acetone
toluene
4-methylpentan-2-one
n-butyl acetate

· **Hazard statements**

H222 *Extremely flammable aerosol.*
H280 *Contains gas under pressure; may explode if heated.*
H319 *Causes serious eye irritation.*
H351 *Suspected of causing cancer.*
H361 *Suspected of damaging fertility or the unborn child.*
H336 *May cause drowsiness or dizziness.*
H372-H373 *Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.*

· **Precautionary statements**

P201 *Obtain special instructions before use.*
P202 *Do not handle until all safety precautions have been read and understood.*
P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Pressurized container: Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P264 *Wash thoroughly after handling.*
P270 *Do not eat, drink or smoke when using this product.*
P271 *Use only outdoors or in a well-ventilated area.*
P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P308+P313 *IF exposed or concerned: Get medical advice/attention.*
P312 *Call a poison center/doctor if you feel unwell.*
P314 *Get medical advice/attention if you feel unwell.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
P405 *Store locked up.*
P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

USA

(Contd. on page 15)

Trade name: 19353 Toyota Red Pearl 3R3

(Contd. of page 14)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 03/14/2018 / 15

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**