

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 07/30/2019

Revision date: 07/31/2019

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1K Plastic Adhesion Promoter
Product code : 3680009 / REZ353

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinsh

1.3. Details of the supplier of the safety data sheet

Manufacturer

Peter Kwasny GmbH
Heilbronner Str. 96
Gundelshheim, 74831 – Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
2275 Lake Shore Boulevard West, Suite 530
Toronto, ON M8V 3Y3

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Carc. 2
Repr. 2
Asp. Tox. 1
Simple Asphy

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways. May displace oxygen and cause rapid suffocation.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If exposed or concerned: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Dimethyl ether	(CAS-No.) 115-10-6	30-60
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	10-30
n-Butyl acetate	(CAS-No.) 123-86-4	10-30
Ethylbenzene	(CAS-No.) 100-41-4	1-5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
- Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide (CO₂).
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing vapours, spray, mist, gas, fume, dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethyl ether (115-10-6)		
Not applicable		
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
n-Butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
IDLH	US IDLH (ppm)	1700 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

n-Butyl acetate (123-86-4)		
NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm
Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (-0.4 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.74 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)

LC50 inhalation rat	164000 ppm/4h
---------------------	---------------

Xylenes (o-, m-, p- isomers) (1330-20-7)

LD50 oral rat	3500 mg/kg
---------------	------------

LD50 dermal rabbit	> 4350 mg/kg
--------------------	--------------

LC50 inhalation rat	29.08 mg/l/4h
---------------------	---------------

n-Butyl acetate (123-86-4)

LD50 oral rat	10768 mg/kg
---------------	-------------

LD50 dermal rabbit	> 17600 mg/kg
--------------------	---------------

LC50 inhalation rat	390 ppm/4h
---------------------	------------

Ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg
---------------	------------

LD50 dermal rabbit	15400 mg/kg
--------------------	-------------

LC50 inhalation rat	17.4 mg/l/4h
---------------------	--------------

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Suspected of causing cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
--	---------------------------------

In OSHA Hazard Communication Carcinogen list	Yes
--	-----

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified.

STOT-repeated exposure : Not classified.

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Aspiration hazard : May be fatal if swallowed and enters airways.

Plastic Adhesion Promoter	
Vaporizer	Aerosol

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
n-Butyl acetate (123-86-4)	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Ethylbenzene (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

12.2. Persistence and degradability

Plastic Adhesion Promoter	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Plastic Adhesion Promoter	
Bioaccumulative potential	Not established.
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 – 15
Partition coefficient n-octanol/water	2.77 - 3.15
n-Butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1.81 (at 23 °C)
Ethylbenzene (100-41-4)	
BCF fish 1	15
Partition coefficient n-octanol/water	3.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

1K Plastic Adhesion Promoter

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
- Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

- UN-No.(DOT/TDG) : UN1950
- Proper Shipping Name (DOT/TDG) : Aerosols
- Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

- Revision date : 07/31/2019
- Other information : None.
- Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.