

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 07/30/2019

Revision date: 07/31/2019

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1K Self Etch Primer Light Gray
Product code : 3680003 / REZ931

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinish

1.3. Details of the supplier of the safety data sheet

Manufacturer

Peter Kwasny GmbH
Heilbronner Str. 96
Gundelsheim, 74831 – Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
2275 Lake Shore Boulevard West, Suite 530
Toronto, ON M8V 3Y3

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Eye Irrit. 2A
Skin Sens. 1
Repr. 2
Simple Asphy

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS04

GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Dimethyl ether	(CAS-No.) 115-10-6	30-60
Acetone	(CAS-No.) 67-64-1	15-40
n-Propanol	(CAS-No.) 71-23-8	10-30
Isobutyl alcohol	(CAS-No.) 78-83-1	5-10
Titanium dioxide	(CAS-No.) 13463-67-7	5-10
Bisphenol A-epichlorohydrin polymer	(CAS-No.) 25068-38-6	1-5
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	0.1-1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide (CO₂).
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Halogenated compounds.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethyl ether (115-10-6)		
Not applicable		
Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
n-Propanol (71-23-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

n-Propanol (71-23-8)		
OSHA	OSHA PEL (TWA) (mg/m ³)	500 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	500 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	625 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
Isobutyl alcohol (78-83-1)		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	1600 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	150 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Bisphenol A-epichlorohydrin polymer (25068-38-6)		
Not applicable		
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Wear eye/face protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol
Colour	: Light gray
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Flash point	: < -18 °C (-0.4 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.79 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Halogenated compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Dimethyl ether (115-10-6)	
LC50 inhalation rat	164000 ppm/4h

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	50100 mg/m ³ (Exposure time: 8 h)

n-Propanol (71-23-8)	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4049 mg/kg
LC50 inhalation rat	> 13548 ppm/4h

Isobutyl alcohol (78-83-1)	
LD50 oral rat	2460 mg/kg

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isobutyl alcohol (78-83-1)	
LD50 dermal rabbit	3400 mg/kg
LC50 inhalation rat	> 6.5 mg/l/4h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 oral rat	11400 mg/kg

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat	29.08 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.

1K Self Etch Primer Light Gray	
Vaporizer	Aerosol

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

Acetone (67-64-1)	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

n-Propanol (71-23-8)	
LC50 fish 1	4480 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3642 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	3339 - 3977 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Isobutyl alcohol (78-83-1)	
LC50 fish 1	1370 - 1670 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	1300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	375 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	1070 - 1933 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

12.2. Persistence and degradability

1K Self Etch Primer Light Gray	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

1K Self Etch Primer Light Gray	
Bioaccumulative potential	Not established.

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18

Acetone (67-64-1)	
BCF fish 1	0.69
Partition coefficient n-octanol/water	-0.24

n-Propanol (71-23-8)	
Partition coefficient n-octanol/water	0.25 - 0.34

Isobutyl alcohol (78-83-1)	
BCF fish 1	(no bioconcentration expected)
Partition coefficient n-octanol/water	0.79 (at 25 °C)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 - 15
Partition coefficient n-octanol/water	2.77 - 3.15

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950
Proper Shipping Name (DOT/TDG) : Aerosols
Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

1K Self Etch Primer Light Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - WARNING: This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 07/31/2019
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.