



The United States of America:  
Peter Kwasny Inc.  
62-64 Enter Lane,  
Islandia, NY 11749

Distributed in

Canada by  
Peter Kwasny Spraypaint Canada Inc.  
2275 Lakeshore Blvd. West, Suite 530  
Toronto, ON. M8V 3Y3

Toll free North America  
Phone: 1-844-426-6330 / Fax: 1-866-226-6434  
order@kwasny.us / service@kwasny.us  
www.spraymax.com

**SprayMax®**  
**1K Wax & Grease Remover**  
**314 g NET WT. 11.1 oz**  
**Art. Nr. 3680094**



## Product

### Description / Purpose

Waterborne cleaning agent, rich in active ingredients and with a reduced solvent content. Ideal for the removal of silicone, grease, oil, wax, dirt, tar, and soot. This high quality product improves the adhesion to any paint coat and reduces the electrostatic effect. High cleaning and degreasing properties. The product is used for the application of waterborne basecoats.

### Properties

- Increases adhesion
- Maximum yield
- Uniform distribution
- Strong cleaning and degreasing effect
- Reduces electrostatic effect
- Especially for application of waterborne basecoats and special coatings.
- High penetration level for plastic parts
- Provides on anti-static effect to plastic parts

<b>Material base</b>	Combination of water and solvent resins
<b>Colour</b>	Transparent
<b>EPA Coating Category</b>	n.a.
<b>CARB Aerosol Rule Coating Category (01/2017)</b>	n.a.

**Substrate**

Metal, plastics, glass, old paint and factory paint which has been filled and primed; Coated and uncoated surfaces. Headlight polycarbonate lenses.


**Processing**

**Protection measures**




Wear personal protection equipment. (respiratory mask/gloves/goggles)  
For more information, see safety data sheet.

**Spraying distance**



6 - 8 inches / 15 - 20 cm

**Spray passes**




1 light spray coat directly before applying the next paint coat and wipe it immediately using a clean, dry cloth. Only clean small areas in parallel. In case of heavy contamination repeat the cleaning process. Don't use contaminated clothes. Change the clothes more often.

**Processing conditions**




Optimum application at 64° F - 77° F (18° C - 25° C) and a relative humidity from 40 - 50 %.

**Coverage**



approx. 8 - 11 sq ft (0.75 - 1 m<sup>2</sup>) / aerosol


**Finish**



After painting, turn the can upside down and spray the valve until empty.

## **Additional Information**

### **Shelf Life**



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 60° F - 77° F / 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

### **Disposal**



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

### **Note**

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.