

USA SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: FUSOR 130 RIGID FOAM PT B

Product Use/Class: Urethane, Pt 2 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 07/01/2016

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Acute toxicity DermalCategory 4

Acute toxicity Inhalation - Vapours Category 4 - 93% of the mixture consists of ingredient(s) of unknown toxicity. Acute toxicity Inhalation - Dust and Mist Category 4 - 94% of the mixture consists of ingredient(s) of unknown toxicity.

Skin corrosion/irritation Category 1B

Serious eye damage/eye irritation Category 1

Reproductive toxicity Category 2

Specific target organ systemic toxicity (single exposure) Category 2 Central nervous system Specific target organ systemic toxicity (repeated exposure) Category 1 upper respiratory system Specific target organ systemic toxicity (repeated exposure) Category 2 Respiratory system

GHS LABEL ELEMENTS:

Symbol(s)







Signal Word

DANGER

Hazard Statements

Harmful in contact with skin.

Harmful if inhaled.

Causes severe skin burns and eye damage.

Causes serious eye damage.

Suspected of damaging fertility or the unborn child.

May cause damage to organs.(Central nervous system)

Causes damage to organs through prolonged or repeated exposure.(upper respiratory system)

May cause damage to organs through prolonged or repeated exposure.(Respiratory system)

Precautionary Statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Response

Immediately call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Wash contaminated clothing before reuse.

Storage

Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Causes respiratory tract irritation. May be severely irritating to the nose, throat and respiratory tract. Harmful if absorbed through skin. Can burn mouth, throat, and stomach. Allergic conditions can occur in certain individuals with high sensitivity to isocyanates; this may result in asthma-like symptoms.

Chronic: Prolonged or repeated contact may result in dermatitis. May cause kidney damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Dimethylethanolamine	108-01-0	5 - 10 %
Amine catalyst	PROPRIETARY	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Water Fog, Foam UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

Product: FUSOR 130 RIGID FOAM PT B. Effective Date: 07/01/2016

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

Chemical Name	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	Skin
Dimethylethanolamine	N.E.	N.E.	N.E.	N.E.	N.A.
Amine catalyst	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR: Amine VAPOR PRESSURE: N.D.

Product: FUSOR 130 RIGID FOAM PT B, Effective Date: 07/01/2016

APPEARANCE: Amber VAPOR DENSITY: Heavier than Air

PHYSICAL STATE:LiquidLOWER EXPLOSIVE LIMIT:2%(V)FLASH POINT: ≥ 201 °F, 93 °CUPPER EXPLOSIVE LIMIT:10%(V)

Cleveland Open Cup

BOILING RANGE: 100 °C EVAPORATION RATE: Slower than n-butyl-

acetate

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 1.08 g/cm3 - 9.00 lb/gal

DECOMPOSITION TEMPERATURE:
ODOR THRESHOLD:
SOLUBILITY IN H2O:N.D.VISCOSITY, DYNAMIC:
VISCOSITY, KINEMATIC:
VOLATILE BY WEIGHT:N.D.2.00 %

 SOLUBILITY IN H2O:
 Insoluble
 VOLATILE BY WEIGHT:
 2.00 %

 pH:
 N.A.
 VOLATILE BY VOLUME:
 2.00 %

 FREEZE POINT:
 N.D.
 VOC CALCULATED:
 0 lb/gal, 0 g/l

COEFFICIENT OF WATER/OIL N.D.

DISTRIBUTION:

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, organic or inorganic nitrogen compounds including traces of hydrogen cyanide, Nitric acid, Ammonia, Oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	<u>LD50/LC50</u>		
Dimethylethanolamine	Oral LD50: Rat 1,803 mg/kg		
	Dermal LD50: Rabbit 1,220 mg/kg		
	Inhalation LC50: Rat 1641 ppm/4 h		
Amine catalyst	Oral LD50: Rat 1,700 mg/kg		
-	Dermal LD50: Rabbit 3,200 mg/kg		

Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child.

Components contributing to classification: Amine catalyst.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	<u>Ecotoxicity</u>
Dimethylethanolamine	<u>Fish:</u> Pimephales promelas 81 mg/l96 h Static <u>Invertebrates:</u> Daphnia magna 98.77 mg/l48 h <u>Plants:</u> Desmodesmus subspicatus 35 mg/l72 h
Amine catalyst	<u>Fish:</u> Pimephales promelas 1,510 - 1,980 mg/l96 h flow-through

Page: 4

Product: FUSOR 130 RIGID FOAM PT B, Effective Date: 07/01/2016

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

DOT Proper Shipping Name: Corrosive liquids, n.o.s.

DOT Hazard Class:8SECONDARY HAZARD:NoneDOT UN/NA Number:1760

Packing Group: III Emergency Response Guide Number: 154

IATA Cargo

PROPER SHIPPING NAME: Corrosive liquids, n.o.s.

DOT Hazard Class: 8
HAZARD CLASS: None
UN-NUMBER: 1760
PACKING GROUP: III
EMS: 8L

IMDG

PROPER SHIPPING NAME: Corrosive liquid, n.o.s.

DOT Hazard Class: 8
HAZARD CLASS: None
UN-NUMBER: 1760
PACKING GROUP: III
EMS: F-A

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

NONE

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

Page: 5

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 1 PHYSICAL HAZARD: 0

* - Indicates a chronic hazard; see Section 2

Revision: Section 2

Effective Date: 07/01/2016

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.