



## PART NUMBER

Norton Amber Rustproofing  
636425**06425**

## PACKAGE SIZE

24 oz. Aerosol, Net Wt. 17.75 fl. oz.  
6/Case

## DESCRIPTION

Amber Rustproofing matches OEM appearance while providing superior rust protection. This abrasion resistant coating will flow into hard to reach seams. It is designed for replacement panels or new car rustproofing and restores the repair of existing corrosion protection to original specifications found on the interior of fender and panel replacements.



## APPLICATION

1. Shake well
2. Clean surface with Norton Panel and Adhesive Cleaner (076607**82780**) or Norton Automotive Panel Waterborne Cleaner/Degreaser (076607**21937**)
3. Holding can 10 - 12 inches from the surface, apply 2 - 3 light even coats. Short, even strokes produce best results.
4. Remove overspray with Norton Panel and Adhesive Cleaner (076607**82780**)
5. For use with Norton Corrosion Protection Wand Kit (636425**06426**) can also be applied using the tubing, included for inside guide rails and other hard to reach applications

*Note: Allow several hours for flammable vapors to escape when product is sprayed in enclosed areas. Flush with compressed air to help remove vapors.*

## SUBSTRATES

Steel, Galvanized, Aluminum

## TECHNICAL DATA

APPEARANCE: Amber

SHELF LIFE: 1 Year

### PERFORMANCE PROPERTIES

TEST	CONDITION	RESULT
Metal Adhesion	1 hour @ 75°F (24°C) after application	Very Good
Water Resistance	3 weeks @ 75°F (24°C)	Excellent (no adhesion loss)

## REGULATORY

Category: Undercoat  
VOC Content: <75% by weight

## PRECAUTIONS

For use only by professional use only. Before use, read and follow all TDS, label and SDS precautions.

