_____SAINT-GOBAIN

Product identifier used on th	
Product Name:	SMC/Fiberglass Adhesive - 3 minute
Other means of identification	
Product Codes:	63642504671
Recommended use of the che	emical and restrictions on use:
Product Uses:	Adhesives Industrial chemical
Product Restrictions:	For Professional Use Only
Chemical manufacturer addre	ess and telephone number:
Manufacturer Name:	Saint-Gobain Abrasives, Inc.
Manufacturer Address 1:	1 New Bond Street
Manufacturer City:	Worcester
Manufacturer State:	MA
Manufacturer Zip Code:	01615
Manufacturer Country:	USA
Manufacturer Web:	www.Nortonabrasives.com
Business Phone:	508-795-5000
Distributor:	Saint-Gobain Canada, Inc.
Distributor Address 1:	28 Albert St, W.
Distributor City:	Plattsville
Distributor State:	ON
Distributor ZipCode:	N0J 1S0
Distributor Country:	Canada
Distributor Web:	www.Nortonabrasives.com
Distributor Phone:	519-684-7441
Emergency phone number:	
Emergency Phone:	508-795-5000
Creation Date:	2018-11-01
Revision Date:	2019-01-17 17:13:46

Page 2 of 21 Notes from Section 1: CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300 For emergencies in Canada, call CHEMTREC: 800-424-930029 CFR 1910.1200 (OSHA HazCom 2012) PART A NFPA: Health: 2 Flammability: 1 Instability: 1 HMIS III: HEALTH: 2* FLAMMABILITY: 1 PHYSICAL HAZARD: 1 0 = Not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic NFPA Flammable and Combustible Liquids Classification: Combustible Liquid Class IIIB PART B NFPA: Health: 2 Flammability: 1 Instability: HMIS III: HEALTH: 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 0 = Not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic NFPA Flammable and Combustible Liquids Classification: Combustible Liquid Class IIIB Section 2: Hazards Identification Classification of the chemical in accordance with CFR 1910.1200(d)(f): Signal Words: Danger **GHS Class:** Skin Irritation, category 2 Eye Irritation, category 2A Respiratory sensitisation, category 1 Skin Sensitization, category 1 Reproductive toxicity, category 2 Specific target organ systemic toxicity - single exposure: Category3 (Respiratory system) Specific target organ systemic toxicity - repeated exposure(Inhalation): Category 2 (Respiratory system, Respiratory Tract)

		Page
Hazard Statements:	H315 - Causes skin irritation.	
	H317 - May cause an allergic skin reaction.	
	H318 - Causes serious eye damage.	
	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
	H335 - May cause respiratory irritation.	
	H361 - Suspected of damaging fertility or the unborn child.	
	H373 - May cause damage to organs (Respiratory system, Respiratory Tract)	
	through prolonged or repeated exposure if inhaled.	
Precautionary Statements:	P201 - Obtain special instructions before use.	
	P202 - Do not handle until all safety precautions have been read and understood.	
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.	
	P264 - Wash skin thoroughly after handling.	
	P271 - Use only outdoors or in a well-ventilated area.	
	P272 - Contaminated work clothing should not be allowed out of the workplace.	
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.	
	P285 - In case of inadequate ventilation wear respiratory protection.	
	P302+P352 - IF ON SKIN: Wash with plenty of soap and water.	
	P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position	
	comfortable for breathing.	
	P312 - Call a POISON CENTER or doctor/physician if you feel unwell.	
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.	
	Remove contact lenses, if present and easy to do. Continue rinsing.	
	P308+P313 - IF exposed or concerned: Get medical advice/attention.	
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.	
	P337+P313 - If eye irritation persists: Get medical advice/attention.	
	P362 - Take off contaminated clothing and wash before reuse.	
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.	
	P405 - Store locked up.	
	P501 - Dispose of contents/ container to an approved waste disposal plant.	

Hazards not otherwise classified that have been identified during the classification process:

Section 3: Composition/Information on Ingredients

Mixtures:

Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
POLYMER		Concentration: > = 10.00 - < 15.00%		
SCAVENGER		Concentration: > = 10.00 - < 15.00%		
URETHANE PREPOLYMER		Concentration: > = 5.00 - < 10.00%		
4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8	Concentration: 35.51%		
TALC	14807-96-6	Concentration: 10.22%		
PROPYLENE CARBONATE	108-32-7	Concentration: 1.49%		
TALC	14807-96-6	Concentration: 22.73%		
PIPERAZINE	110-85-0	Concentration: 0.76%		

TALC:

Comments:

PART B: Substance/Mixture: Mixture

Classification: Thismaterial is not consideredhazardous under the OSHA Hazard Communication Standard(HazCom 2012).

SCAVENGER:

Comments:	PART A: Substance/Mixture: Mixture	
	CAS-No.: 254504001-5709	
	Classification: Thismaterial is not consideredhazardous under the OSHA Hazard Communication Standard(HazCom 2012).	
TALC:		
Comments:	The identity of one or more component(s) is being withheld under business confidentiality.	
	Classification: Thismaterial is not consideredhazardous under the OSHA Hazard Communication Standard(HazCom 2012).	
4,4'-DIPHENYLMETHANE	DIISOCYANATE:	
Comments:	The identity of one or more component(s) is being withheld under business confidentiality.	
	Classification:	
	Acute Tox. 4; H332	
	Skin Irrit. 2; H315 Eye Irrit. 2A; H319	
	Resp. Sens. 1; H334	
	Skin Sens. 1; H317	
	STOT SE 3; H335	
PROPYLENE CARBONATE:	STOT RE 2; H373	
Comments:	The identity of one or more component(s) is being withheld under business confidentiality.	
	Classification: Eye Irrit. 2A; H319	
POLYMER:		
Comments:	PART A:	
	Substance/Mixture: Mixture	
	CAS-No.: 254504001-5759	
	Classification:	
	Acute Tox. 4; H332	
	Skin Irrit. 2; H315 Resp. Sens. 1A; H334	
	Skin Sens. 1A; H317	
	STOT SE 3; H335	
	STOT RE 2; H373	
URETHANE PREPOLYMER		
Comments:	PART A:	
	Substance/Mixture: Mixture	
	CAS-No.: 800986-5572P	
	Classification:	
	Resp. Sens. 1; H334	
	Skin Sens. 1; H317	
PIPERAZINE:		

PART B: Substance/Mixture: Mixture

Classification: Flam. Sol. 1; H228 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1B; H334 Skin Sens. 1B; H317 Repr. 2; H361

Section 4: First Aid Measures

Description of necessary measures:

Eye Contact:	In case of eye contact: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
Skin Contact:	In case of skin contact: Remove contaminated clothing. If irritation develops, get medicalattention. If on skin, rinse well with water. Wash contaminated clothing before re-use.
Inhalation:	If inhaled: Move to fresh air. Call a physician or poison control centre immediately. Keep patient warm and at rest. If unconscious place in recovery position and seek medical advice.
Ingestion:	If swallowed: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything bymouth to an unconscious person. If symptoms persist, call a physician.
Most important sympto	ms/effects, acute and delayed:

Indication of immediate medical attention and special treatment needed

Note To Physicians:

No hazards which require special first aid measures.

Notes from Section 4:	General advice:
	Move out of dangerous area.
	Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
	Show this safety data sheet to the doctor in attendance.
	Do not leave the victim unattended.
	Most important symptoms and effects, both acute and delayed:
	Pulmonary edemamay be delayed.
	Signs and symptoms of exposure to this material through breathing, swallowing,
	and/or passage of thematerial through the skinmay include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat,
	airways)
	Cough
	Headache
	Chest pain
	Lung edema (fluid buildup in the lung tissue)
	Difficulty in breathing
	Causes skin irritation.
	May cause an allergic skin reaction.
	Causes serious eye irritation.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	May cause respiratory irritation.
	Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled
	May cause damage to organs through profonged of repeated exposure if hinared
Section 5: Firefighting Mea	nguishing media
	nguishing media
Suitable and unsuitable extin	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray
Suitable and unsuitable extin	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstance: and the surrounding environment. Water spray Foam
Suitable and unsuitable extin	aguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2)
Suitable and unsuitable extin	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstance: and the surrounding environment. Water spray Foam
Suitable and unsuitable extin	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting
Suitable and unsuitable extin Extinguishing Media:	 Iguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents.
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media:	 Iguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet.
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from	 Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet.
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	 Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from	 Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid)
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	 Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) lsocyanates
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	 Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid)
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOx) Toxic fumes
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	nguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOx)
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	Inguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOx) Toxic fumes Aldehydes
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	Inguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOX) Toxic fumes Aldehydes Ketones Halogenated hydrocarbons Nitrogen oxides (NOX)
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	Impuision gradia Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOx) Toxic fumes Aldehydes Ketones Halogenated hydrocarbons Nitrogen oxides (NOx) Bromine
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion	Inguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOX) Toxic fumes Aldehydes Ketones Halogenated hydrocarbons Nitrogen oxides (NOX)
Suitable and unsuitable extin Extinguishing Media: Unsuitable Media: Specific hazards arising from Hazardous Combustion Products:	Aguishing media Suitable: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical Specific extinguishing methods: Product is compatible with standard fire-fighting agents. High volume water jet. the chemical Carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid) Isocyanates Nitrogen oxides (NOx) Toxic fumes Aldehydes Ketones Halogenated hydrocarbons Nitrogen oxides (NOx) Bromine

Protective Equipment:	Special protective equipment for firefighters: In the event of fire, we contained breathing apparatus.
NFPA Health:	2
NFPA Fire:	1
NFPA Reactivity:	1

Notes from Section 5:	Specific hazards during firefighting: Do not allow run-off from fire fighting to ented drains or water courses.
	Further information: Fire residues and contaminated fire extinguishing watermust be disposed of in accordance with local regulations.
Section 6: Accidental Releas	se Measures
Personal precautions, protecti	ive equipment and emergency procedures
Personnel Precautions:	Personalprecautions, protective equipment and emergency procedures: Use personal protective equipment. Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Methods and materials for cor	ntainment and cleaning up
Methods for Containment:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Methods for Cleanup:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Environmental precautions	
Environmental Precautions:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Notes from Section 6:	Other information: Comply with all applicable federal, state, and local regulation
Section 7: Handling and Stor	
Handling:	 Advice on safe handling: Avoid formation of aerosol. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes.
	Smoking, eating and drinking should be prohibited in the applicationarea. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
Hygiene Practices:	Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.
Hygiene Practices: Conditions for safe storage, inc	When using do not eat or drink. When using do not smoke.
	When using do not eat or drink. When using do not smoke.

Section 8: Exposure Controls/Personal Protection

Exposure limit:	Components with workplace control parameters:
	PART A:
	Components: SCAVENGER
	CAS-No.: 254504001-5709
	ACGIH TWA: 1 mg/m3 Respirable fraction.
	Components: 4,4'-DIPHENYLMETHANE DIISOCYANATE
	CAS-No.: 101-68-8
	ACGIH TWA: 0.005 ppm
	NIOSH/GUIDE REL: 0.005 ppm, 0.05 mg/m3
	NIOSH/GUIDE Ceil_Time: 0.020 ppm, 0.2 mg/m3
	OSHA_TRANS Ceiling: 0.02 ppm, 0.2 mg/m3
	Components: TALC
	CAS-No.: 14807-96-6
	ACGIH TWA: 2 mg/m3 Respirable fraction.
	NIOSH/GUIDE REL: 2 mg/m3 Respirable.
	Z3 TWA: 0.1 mg/m3 Respirable.
	Z3 TWA: 0.3 mg/m3 Total dust.
	PART B:
	Components: TALC
	CAS-No.: 14807-96-6
	ACGIH TWA: 2 mg/m3 Respirable fraction.
	NIOSH/GUIDE REL: 2 mg/m3 Respirable.
	Z3 TWA: 0.1 mg/m3 Respirable. Z3 TWA: 0.3 mg/m3 Total dust.
	Components: PIPERAZINE
	CAS-No.: 110-85-0
	ACGIH TWA: 0.03 ppm Inhalablefraction and vapor (as piperazine)
	ACGIHLIS_P TWA: 0.03 ppm Inhalablefraction and vapor (as piperazine)
Appropriate engineering co	ontrols
Engineering Controls:	Provide sufficientmechanical (general and/or local exhaust) ventilation tomaintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Individual protection meas	ures
Eye Protection:	Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
Skin Protection:	Wear as appropriate: Impervious clothing
	Safetyshoes Choose body protection according to the amount and concentration of the
	dangerous substance at the work place.
	Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
	Remarks: The suitability for a specific workplace should be discussed with the
Hand Protection:	nemary, the subaying for a specific workplace should be discussed with the

Respiratory Protection:	In the case of vapour formation use a respirator with an approved filter. Diisocyanates have poor warning properties. An air-purifying respirator with an organic vapor cartridge and an N95 prefilter can be used safely and effectively to reduce exposure, provided that appropriate cartridge change schedules are developed to ensure that cartridges are changed before breakthrough occurs. The employer is required to select the appropriate respirator for each situation and must consider potential exposure to chemicals in addition to diisocyanates.
Other Protective:	Body Protection: Wear as appropriate: Impervious clothing Safetyshoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
Hygiene Practices:	Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

Section 9: Physical and Chemical Properties

Physical and chemical properties

Physical State:	PART A: Liquid PART B: Liquid
Color:	PART A: Beige
Odor:	PART A: No data available. PART B: No data available.
pH:	PART A: No data available. PART B: No data available.
Boiling Temperature:	PART A: > 392 deg F/> 200 deg C
Flash Point:	PART A: > 212 deg F/> 100 deg C PART B: > 200.1 deg F/> 93.4 deg C
Flash Point Method:	PART B: Seta closed cup
Lower Flammable Limit:	PART A: No data available. PART B: No data available.
Upper Flammable Limit:	PART A: No data available. PART B: No data available.
Decomposition Temperature:	Thermal decomposition: PART A: No data available. PART B: No data available.
Vapor Pressure:	PART A: < 0.01333 hPa (25 deg C) PART B: 3 hPa (25 deg C) Calculated Vapor Pressure
Vapor Density:	Relative: PART A: > 1 AIR=1 PART B: > 1 AIR=1
Density:	PART A: 1.288 g/cm3 (20 deg C) PART B: 1.225 g/cm3 (20 deg C)
	Relative density: PART A: No data available. PART B: 1.225 (25 deg C)

Page 9 of 21

		Page 10 of 21
Solubility:	Solubility in other solvents:	
	PART A: No data available.	
	PART B: No data available.	
Solubility In Water:	PART A: Practically insoluble.	
	PART B: No data available.	
Evaporation Rate:	PART A: < 1 n-Butyl Acetate	
	PART B: 1 Ethyl Ether	
Viscosity:	Viscosity, kinematic:	
	PART A: No data available.	
	PART B: No data available.	
Odor Threshold:	PART A: No data available.	
	PART B: No data available.	
Octanol Water Partition Coef:	PART A: No data available.	
	PART B: No data available.	
Dynamic Viscosity:	PART A: ca. 20,000 mPa.s	
	PART B: No data available.	
Oxidizing Properties:	PART A: No data available.	
	PART B: No data available.	
Note from Section 9:	Appearance:	
	PART A: Viscous	

Section 10: Stability and Reactivity

Reactivity:

Reactivity:	No decomposition if stored and applied as directed.	
Chemical Stability:		
Chemical Stability:	Stable under recommended storage conditions.	
Possibility of hazardous react Conditions To Avoid:	tions:	
Conditions To Avoid:	Heat Freezing temperatures. Exposure to moisture	
Incompatible Materials:		
Incompatible Materials:	Acids Alcohols Aluminum Amines Ammonia Bases Copper Alloys Fluorides Iron Isocyanates Oxidizingagents Oxidizers Phosphoruscompounds Strong alkalis Strong reducing agents Water Zinc Humid air	

Hazardous Decomposition Products:	Carbon dioxide and carbon monoxide Hydrocarbons
	Hydrogen cyanide (hydrocyanic acid)
	lsocyanates Nitrogen oxides (NOx)
Notes from Section 10:	
Notes nom section 10.	Possibility of hazardous reactions: Product will not undergo hazardous polymerization.

Section 11: Toxicological Information

Toxicological Information:

Product:	
Acute Toxicity:	Not classified based on available information.
Route of Exposure:	Information on likely routes of exposure: Inhalation Skin contact Eye Contact Ingestion
Carcinogenicity:	Not classified based on available information.
	Product: Carcinogenicity - Assessment: Methylene bisphenylisocyanate (MDI) aerosol has been reported to be irritating to lungs at a concentration of 1 mg/m3 with no effect observed at 0.2 mg/m3. Although MDI has been reported to cause an increase in non-carcinogenic lung tumors and a single carcinogenic lung tumor at very high concentrations (6mg/m3), it is not classified as a carcinogen by IARC, NTP or OSHA.
Mutagenicity:	Germ cell mutagenicity: Not classified based on available information.
Reproductive Toxicity:	Suspected of damaging fertility or the unborn child.
Irritation:	Skin corrosion/irritation: Causes skin irritation. Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation: Causes serious eye irritation.
	Product: Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.
Sensitization:	Respiratory or skin sensitisation: Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
OSHA Carcinogen:	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen byOSHA.
NTP Carcinogen:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen byNTP.
Notes from Section 11:	Further information Product: Remarks: No data available.
TALC:	
IARC Carcinogen:	Group 2B: Possibly carcinogenic to humans.
SCAVENGER:	

Page 11 of 21

Irritation:	Skin corrosion/irritation:
	Result: Possibly irritating to skin.
	Serious eye damage/eye irritation: Result: Mildly irritating to eyes.
ALC:	
Irritation:	Skin corrosion/irritation: Result: Possibly irritating to skin.
	Serious eye damage/eye irritation: Result: Possibly irritating to eyes.
,4'-DIPHENYLMETHANE DIISO	CYANATE:
Skin Toxicity:	Acute dermal toxicity: LD 50 (Rabbit): > 7,900 mg/kg
Ingestion Toxicity:	Acute oral toxicity: LD 50 (Rat): 9,200 mg/kg
Inhalation Toxicity:	Acute inhalation toxicity: LC 50 (Rat): 0.369 mg/l Exposure time: 4 h
	LC 50 (Rat): > 2.24 mg/l Exposure time: 1 h Test atmosphere: Dust/mist Method:OECD Test Guideline 403 Assessment: The component/mixture is classified as acute inhalation toxicity, category 4.
Irritation:	Skin corrosion/irritation: Result: Irritating to skin.
	Serious eye damage/eye irritation: Result: Irritating to eyes.
Sensitization:	Respiratory or skin sensitisation: Assessment: May cause sensitization by inhalation. Assessment: May cause sensitization by skin contact.
Notes from Section 11:	Further information Product: Remarks: Lung
ROPYLENE CARBONATE:	
Skin Toxicity:	Acute dermal toxicity: LD 50 (Rabbit): > 24 g/kg
Ingestion Toxicity:	Acute oral toxicity: LD 50 (Rat): 29.1 g/kg
Mutagenicity:	Germ cell mutagenicity: Genotoxicity in vitro: Test Type: Ames test Test species: Salmonella typhimurium Metabolic activation: With and withoutmetabolic activation Method: OECD Test Guideline 471 Result: Negative
	Genotoxicity in vivo: Test Type: Micronucleus test Test species: Mouse Cell type: Bone marrow Method: OECD Test Guideline 474 Result: Negative

.....

Irritation:	Skin corrosion/irritation:
initation.	Species: Rabbit
	Method: OECD Test Guideline 404
	Result: Not irritating to skin
	Serious eye damage/eye irritation:
	Species: Rabbit
	Result: Irritating to eyes
	Method:OECD Test Guideline 405
POLYMER:	
Skin Toxicity:	Acute dermal toxicity: (Rabbit): > 9,400 mg/kg
	Remarks: Information given is based on data obtained from similar
	substances.
Ingestion Toxicity:	Acute oral toxicity:
	LD 50 (Rat): > 5,000 mg/kg
	Method: OECD Test Guideline 425
	GLP: Yes
Inhalation Toxicity:	Acute inhalation toxicity: Assessment: The component/mixture is classified a
	acute inhalation toxicity, category 4.
Mutagenicity:	Germ cell mutagenicity:
	Genotoxicity in vitro:
	Test Type: Ames test
	Result: Negative
	Remarks: Information given is based on data obtained from
	similarsubstances.
	Genotoxicity in vivo:
	Test Type: In vivo micronucleus test
	Test species: Rat
	Method: OECD Test Guideline 474
	Remarks: Information given is based on data obtained from
	similarsubstances.
Irritation:	Skin corrosion/irritation:
	Result: Irritating to skin.
	Remarks: Information given is based on data obtained from similar substances.
	Serious eye damage/eye irritation: Result: Not irritating to eyes.
	Result: Not irritating to eyes. Remarks: Information given is based on data obtained from similar
	substances.
Sensitization:	Respiratory or skin sensitisation:
	Test Type: Maximisation Test (GPMT)
	Species: Guinea pig
	Assessment: May cause sensitization by skin contact.
	Result: The product is a skin sensitiser, sub-category 1A.
	Assessment: May cause sensitization by inhalation.
	Result: The product is a respiratory sensitiser, sub-category 1A.
URETHANE PREPOLYMER:	
Irritation:	Skin corrosion/irritation:
	Result: Not irritating to skin.
	Serious eye damage/eye irritation:

Sensitization:	Respiratory or skin sensitisation: Assessment: May cause sensitization by skin contact. Assessment: May cause sensitization by inhalation.
IPERAZINE:	
Ingestion Toxicity:	Acute oral toxicity: LD50 (Rat): ca. 2,600 mg/kg Method: OECD Test Guideline 401
Inhalation Toxicity:	Acute inhalation toxicity: LCO (Rat, male and female): 1.61 mg/l Exposure time: 8 h Test atmosphere: Vapour
Reproductive Toxicity:	Reproductive toxicity - Assessment: Some evidence of adverse effects or sexual function and fertility, and/or on development, based on animal experiments.
Irritation:	Skin corrosion/irritation: Result: Corrosive after 3 minutes to 1 hour of exposure.
	Serious eye damage/eye irritation: Result: Corrosive to eyes.
Sensitization:	Respiratory or skin sensitisation: Assessment: The product is a respiratory sensitiser, sub-category 1B. Assessment: The product is a skin sensitiser, sub-category 1B.
ction 12: Ecological Inforn 4'-DIPHENYLMETHANE DIISC	
Ecotoxicity:	Toxicity to fish: LC50 (Oryzias latipes (Orange-red killifish)): > 3,000 mg/l Exposure time: 96 h Test Type: semi-static test Remarks: Information given is based on data obtained from similarsubstances.
	Toxicity to daphnia and other aquatic invertebrates: EC50 (Water flea (Daphnia magna)): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity): NOEC (Water flea (Daphnia magna)): > 10 mg/l Exposure time: 21 d End point: Reproduction Test Test Type: Semi-static test Method:OECD Test Guideline 211 Remarks: Information given is based on data obtained from similar substances.

PROPYLENE CARBONATE:

.....

Ecotoxicity:	Toxicity to fish:
,	, LC50 (Cyprinus carpio (Carp)): > 1,000 mg/l
	Exposure time: 96 h
	Test Type: Semi-static test
	Method: Directive 67/548/EEC, Annex V, C.1.
	Toxicity to daphnia and other aquatic invertebrates:
	EC50 (Water flea (Daphnia magna)): > 1,000 mg/l
	Exposure time: 48 h
	Test Type: Static test
	Method: OECD Test Guideline 202
	Toxicity to algae:
	EC50 (Desmodesmus subspicatus (green algae)): > 900 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: Static test
	Method: OECD Test Guideline 201
	NOEC (Desmodesmus subspicatus (green algae)): 900 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: Static test
	Method: OECD Test Guideline 201
OLYMER:	
Ecotoxicity:	Toxicity to fish:
	LC 50 (Oryzias latipes (Japanese medaka)): > 3,000 mg/l
	Exposure time: 96 h
	Test Type: Semi-static test
	Remarks: Information given is based on data obtained from similarsubstances.
	Toxicity to daphnia and other aquatic invertebrates:
	(Daphniamagna (Water flea)): > 1,000 mg/l Exposure time: 24 h
	Test Type: Static test
	Method: OECD Test Guideline 202
	Remarks: Information given is based on data obtained from
	similarsubstances.
	Toxicity to algae:
	NOEC (Desmodesmus subspicatus (green algae)): 1,640 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: static test
	Method: OECD Test Guideline 201
	Remarks: Information given is based on data obtained from
	similarsubstances.
PIPERAZINE:	

Ecotoxicity:	Toxicity to fish:
	LC 50 (Poecilia reticulata (guppy)): > 1,800 mg/l Exposure time: 96 h
	Toxicity to daphnia and other aquatic invertebrates:
	EC 50 (Water flea (Daphnia magna)): 21 mg/l Exposure time: 48 h
	Method: OECD Test Guideline 202
	Toxicity to algae: FC = 0 (Beaudakireknorialla sukaanitata (graan algae)): > 1.000 mg/l
	EC 50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 72 h
	Method: OECD Test Guideline 201
	Tovisity to donknip and other acustic investobrates (Chronic tovisity)
	Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) NOEC (Water flea (Daphnia magna)): 12.5 mg/l
	Exposure time: 21 d
	Method: OECD Test Guideline 211
4,4'-DIPHENYLMETHANE DII	SOCYANATE:
Biodegredation:	Persistence and degradability:
Ŭ	Biodegradability:
	Result: Not biodegradable
	Biodegradation: 0% Exposure time: 28 d Method:OECD TestGuideline 302C
	Remarks: Information given is based on data obtained from similar
	substances.
PROPYLENE CARBONATE:	
Biodegredation:	Persistence and degradability:
	Biodegradability:
	Result: Readily biodegradable Biodegradation: 87.1%
	Exposure time: 29 d
	Method: OECD TestGuideline 301B
POLYMER:	
Biodegredation:	Persistence and degradability:
	Biodegradability:
	Result: Not readily biodegradable. Biodegradation: 0%
	Exposure time: 28 d
	Method: OECD TestGuideline 302C
PIPERAZINE:	
Biodegredation:	Persistence and degradability:
	Biodegradability:
	Result: Readily biodegradable Biodegradation: 70%
	Exposure time: 28 d
	Method: OECD TestGuideline 301F
PROPYLENE CARBONATE:	
BioAccumulation:	Bioaccumulative potential:
	Partition coefficient: n-octanol/water:
	log Pow: -0.41
PIPERAZINE:	

BioAccumulation:	Bioaccumulative potential: Partition coefficient: n-octanol/water: log Pow: -1.17
Mobility in soil:	
Product:	
Notes from Section 12:	Mobility in soil: Components: No data available.
	Other adverse effects: No data available.
	Product: Additional ecological information: No data available.
Section 13: Disposal Consid	erations
Description of waste:	
Waste Disposal:	General advice: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used contair Send to a licensed waste management company.
	Dispose of in accordance with all applicable local, state and federal regulations
Contaminated Packaging:	Emptyremaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recyc or disposal. Do not re-use empty containers.
Section 14: Transport Infor	mation
	U.S. DOT - ROAD: Not dangerous goods.
DOT Other:	U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - INLAND WATER WAYS: Not dangerous goods.
DOT Other: IMDG:	U.S. DOT - RAIL: Not dangerous goods.
	U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - INLAND WATER WAYS: Not dangerous goods. Not dangerous goods.
IMDG:	U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - INLAND WATER WAYS: Not dangerous goods. Not dangerous goods. INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous good INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous
IMDG: IATA Other:	 U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - INLAND WATER WAYS: Not dangerous goods. Not dangerous goods. INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous good INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods. TRANSPORT CANADA - ROAD: Not dangerous goods. TRANSPORT CANADA - RAIL: Not dangerous goods. TRANSPORT CANADA - INLAND WATER WAYS: Not dangerous goods.
IMDG: IATA Other: Canada Other:	 U.S. DOT - RAIL: Not dangerous goods. U.S. DOT - INLAND WATER WAYS: Not dangerous goods. Not dangerous goods. INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods. INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods. TRANSPORT CANADA - ROAD: Not dangerous goods. TRANSPORT CANADA - RAIL: Not dangerous goods. TRANSPORT CANADA - INLAND WATER WAYS: Not dangerous goods. MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIAI

Section 15: Regulatory Information

Safety, health and environmental regulations specific for the product:

.....

Regulatory - Product Based:	
SARA 311/312 Hazards:	
	Acute Health Hazard. Chronic Health Hazard.
California Prop 65:	
	WARNING! This product contains a chemical known to the State of California to
	cause cancer. Components: QUARTZ/SAND
	CAS: 14808-60-7
ARA 311/312 Hazards:	
	Chronic Health Hazard.
SARA 313 Component(s) SARA 313 Component(s)	ARA
313:	
	This material does not contain any chemical components with known CAS numb
	that exceed the threshold (De Minimis) reporting levels established by SARA Tit
	III, Section 313.
California Prop 65:	
	WARNING! This product contains a chemical known to the State of California to
	cause cancer.
	Components: QUARTZ/SAND
	CAS: 14808-60-7
	Components: CARBON BLACK
	CAS: 1333-86-4
TSCA:	
IJCA.	On TSCA Inventory.
DSL:	
	All components of this product are on the Canadian DSL.
AUSTR:	
	On the inventory, or in compliance with the inventory.
ENCO	
ENCS:	Exempt.
KECL:	
	On the inventory, or in compliance with the inventory.
KECL:	
	On the inventory, or in compliance with the inventory.
NICCO	
PICCS:	Not in compliance with the inventory.
IECSC:	
	On the inventory, or in compliance with the inventory.

Inventories:	
	AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA) Registration: Trade Secret
	Chemical Name: POLYMER Identification number: 254504001-5759
	Chemical Name: SCAVENGER Identification number: 254504001-5709
	Chemical Name: URETHANE PREPOLYMER Identification number: 800986-5572P
Regulatory - Ingredient Based:	
4,4'-DIPHENYLMETHANE DIIS	OCYANATE:
CERCLA Reportable Quantity	: Component RQ (lbs): 5000 Calculated product RQ (lbs): 14206.159791
SARA 313 Component(s):	CAS: 101-68-8 %: 35.51%
ection 16: Additional Inform	
Creation Date:	2018-11-01
Revision Date:	2019-01-17 17:13:46
/ersion Number:	1.1
	PART A NFPA: Health: 2 Flammability: 1 Instability: 1
Notes from Section 16:	NFPA: Health: 2 Flammability: 1

NFPA Flammable and Combustible Liquids Classification: Combustible Liquid Class IIIB

PART B NFPA: Health: 2 Flammability: 1 Instability:

HMIS III: HEALTH: 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0

0 = Not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic NFPA Flammable and Combustible Liquids Classification: Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.:

	DT	
N•	RI	$\nu \Lambda$
л.	1 1 1	
A:	п	РА

H228 Flammable solid.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

PART B:

H228 Flammable solid.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H361 Suspected of damaging fertility or the unborn child.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society). CMR: Carcinogenic, Mutagenic or Toxic for Reproduction FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals. H-statement:Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population.

ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit

P-Statement: Precautionary Statement

PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment

STEL: Short-term exposure limit

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

 ${\sf CERCLA}: {\sf Comprehensive Environmental Response, Compensation, and Liability Act}$

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

Page 21 of 21

	PMRA: Health Canada Pest Management Regulatory RTK: Right to Know WHMIS: Work place Hazardous Materials Informatic	
HMIS:	Health 2*	
	Flammability 1	
	Reactivity 1	
	PPE	
	Chronic Health Hazard	
NFPA:	2 1	
Other Information:		
	Copyright © 1996-2019 Enviance Inc. All Rights Reserved.	