

Revision Date 20-Apr-2020

# SAFETY DATA SHEET

Version 2

# **1. IDENTIFICATION**

<u>Product identifier</u> Product Name	EVERCOAT FILLER	
Other means of identification Product Code	100141	
Recommended use of the chemical	and restrictions on use	
Recommended Use	All purpose filler. For professional use only.	
Uses advised against	Uses other than recommended use.	
Details of the supplier of the safety of Manufacturer Address ITW Evercoat A division of Illinois Tool Works Inc. 6600 Cornell Road Cincinnati, OH 45242 USA 513-489-7600 24-hour emergency phone number CHEMTREC: 1-800-424-9300 INTERNATIONAL: 1-703-527-3887	<u>data sheet</u>	May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

E-mail address: Info@evercoat.com

# 2. HAZARDS IDENTIFICATION

### **Classification**

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

### Label elements

### **Emergency Overview**

Signal word	
Danger	
Harmful if swallowed or if inhaled	
Causes skin irritation	
Causes serious eye irritation	
May cause allergy or asthma symptoms or breathing d	ifficulties if inhaled
May cause an allergic skin reaction	
May cause cancer	
Suspected of damaging fertility or the unborn child	

Causes damage to organs through prolonged or repeated exposure Flammable liquid and vapor Appearance Liquid Physical state Liquid Odor Aromatic

### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area In case of inadequate ventilation wear respiratory protection Contaminated work clothing should not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use non-sparking tools Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth In case of fire: Use CO2, dry chemical, or foam to extinguish.

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Unknown acute toxicity

75.68295 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ground Limestone (Calcium	1317-65-3 30 - 6	
Carbonate)		
Styrene	100-42-5	10 - 30
Trade Secret	Proprietary	0.1 - 1
Benzenamine, N,N,4-Trimethyl	99-97-8	0.1 - 1

### **4. FIRST AID MEASURES**

#### **Description of first aid measures**

General advice	Get medical advice/attention if you feel unwell.			
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.			
Skin contact	IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.			
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.			
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.			
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.			
Most important symptoms and effe	ects, both acute and delayed			
Symptoms	See section 2 for more information.			
Indication of any immediate medical attention and special treatment needed				
Note to physicians	Treat symptomatically.			
5. FIRE-FIGHTING MEASURES				

<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Use dry chemical, Foam

Unsuitable extinguishing media None

Specific hazards arising from the chemical Flammable.

Explosion dataSensitivity to Mechanical ImpactNone.Sensitivity to Static DischargeNone.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Remove all sources of ignition. Use personal protective equipment as required.		
Environmental precautions			
Environmental precautions	Do not flush into surface water or sanitary sewer system. See section 12 for additional ecological information.		
Methods and material for containm	ent and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Soak up with inert absorbent material.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.		
Conditions for safe storage, including any incompatibilities			
Storene Conditions	Kaan away from back analys flows and show as your of implicing (i.e. wild lights closely		

Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric
	motors and static electricity).

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ground Limestone (Calcium	-	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> total dust
Carbonate)		TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
1317-65-3		(vacated) TWA: 15 mg/m <sup>3</sup> total	
		dust	
		(vacated) TWA: 5 mg/m <sup>3</sup> respirable	
		fraction	
Styrene	STEL: 20 ppm	TWA: 100 ppm	IDLH: 700 ppm
100-42-5	TWA: 10 ppm	(vacated) TWA: 50 ppm	TWA: 50 ppm
		(vacated) TWA: 215 mg/m <sup>3</sup>	TWA: 215 mg/m <sup>3</sup>
		(vacated) STEL: 100 ppm	STEL: 100 ppm
		(vacated) STEL: 425 mg/m <sup>3</sup>	STEL: 425 mg/m <sup>3</sup>
		Ceiling: 200 ppm	

NIOSH IDLH Immediately Dangerous to Life or Health

**Other Information** 

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.	
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.	
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.	

### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Liquid Physical state Appearance Liquid Aromatic Odor **Odor threshold** No information available **Property** Values No information available pН Melting point / freezing point No information available 145 °C / 293 °F Boiling point / boiling range 32 °C / 90 °F Flash point **Evaporation rate** No information available Flammability (solid, gas) No information available Flammability Limit in Air Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available **Relative density** 1.03 Water solubility No information available Solubility(ies) Insoluble **Partition coefficient** 1.36 Autoignition temperature No information available **Decomposition temperature** No information available No information available **Kinematic viscosity** Dynamic viscosity No information available **Explosive properties** No information available No information available **Oxidizing properties** Other Information No information available Softening point Molecular weight No information available Applied 0.36 lbs/gal or 43 g/L Packaged 1.08 lbs/gal Density 5.8 No information available **Bulk density** SADT (self-accelerating No information available decomposition temperature)

Remarks • Method

## **10. STABILITY AND REACTIVITY**

### Reactivity

No information available

### Chemical stability

Stable under normal conditions

#### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Excessive heat.

# Incompatible materials

Strong oxidizing agents

### **Hazardous Decomposition Products**

Carbon oxides

## **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.			
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.			
Skin contact	May cause skin irritation and/or dermatitis.			
Ingestion	Ingestion may cause irritation to mucous membranes.			

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Styrene	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h	
100-42-5				
Trade Secret	= 5410 mg/kg (Rat)	-	-	
Benzenamine, N,N,4-Trimethyl 99-97-8	= 1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 1400 mg/m³ (Rat)4 h	

### Information on toxicological effects

Symptoms

No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization		ion available.		
Germ cell mutagenicity	No information available. The table below indicates whether each agency has listed any ingredient as a carcinogen.			
Carcinogenicity Chemical Name	ACGIH		NTP	OSHA
Styrene	ACGIN	Group 2A	Reasonably Anticipated	X
100-42-5	A3	Gloup 2A	Reasonably Anticipated	^
Benzenamine,	-	Group 2B	-	Х
N,N,4-Trimethyl				
99-97-8				
IARC (International Age	ency for Research on Cano	er)		
Group 2B - Possibly Card	cinogenic to Humans			
Not classifiable as a hum	an carcinogen			
Group 2A - Probably Car	cinogenic to Humans			
NTP (National Toxicolo	gy Program)			
Reasonably Anticipated -	Reasonably Anticipated to	be a Human Carcinogen		
OSHA (Occupational Sa	afety and Health Administr	ation of the US Departmen	t of Labor)	
X - Present				
Chronic toxicity	toxicity May cause adverse liver effects. Contains a known or suspected reproductive toxin.			
Target Organ Effects				
3	System, Respiratory system, Skin.			, I
	<b>e</b> yete, i te			
The following values are	calculated based on cl	hapter 3.1 of the GHS do	ocument .	
ATEmix (oral)	983 mg/kg			
ATEmix (dermal)	2060 mg/kg	r		
ATEmix (inhalation-d		1		
	usumsy 1.0 mg/l			

### 12. ECOLOGICAL INFORMATION

### Ecotoxicity

# Persistence and degradability No information available.

### **Bioaccumulation**

No information available.

### **Mobility**

No information available.

Chemical Name	Partition coefficient
Styrene 100-42-5	2.95
Benzenamine, N,N,4-Trimethyl 99-97-8	2.81

## Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods			
Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).		
Contaminated packaging	Do not reuse container.		
US EPA Waste Number	D001		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name		California Hazardous Waste Status			
Styrene 100-42-5		Toxic			
		Ignitable			
14. TRANSPORT INFORMATION					
Transportation classifications country variations in regulation		ed to convey all specific regulatory information relating to this product. may vary by container volume and may be influenced by regional or ons. It is the responsibility of the transporting organization to follow all and rules relating to the transportation of the material.			
от					
UN/ID No	UN3269				
Proper shipping name Polyester Resin Kit Hazard Class 3					
Packing Group	111				
ΑΤΑ					
UN/ID No	UN3269				
Proper shipping name	Polyester Resin Kit				
Hazard Class	3				
Packing Group	iii				
ERG Code	No information available.				
MDC					
MDG	1102260				
UN/ID No	UN3269 Delvester Desig Kit				
Proper shipping name	Polyester Resin Kit				

Hazard Class	3
Packing Group	111
EmS-No	No information available

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	Х

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Γ	Styrene	1000 lb	-	RQ 1000 lb final RQ
	100-42-5			RQ 454 kg final RQ

# US State Regulations

### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Styrene	Carcinogen
100-42-5	

Benzenamine, N,N,4-Trimethyl 99-97-8	Carcinogen
Trade Secret	Carcinogen

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ground Limestone (Calcium Carbonate) 1317-65-3	X	X	Х
Styrene 100-42-5	Х	X	Х
Trade Secret	Х	-	-
1,4-NAPHTHOQUINONE 130-15-4	Х	X	Х
Trade Secret	Х	Х	Х

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

### WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards	2	Flammability
HMIS	Health hazards	2	Flammability

20-Apr-2020

ability 3 ability 3 Instability 0 Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

### **Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**