

## 1. IDENTIFICATION

**Product identifier**

**Product Name** EVERCOAT FIBER FILL 4:1

**Other means of identification**

**Product Code** 100736

**Recommended use of the chemical and restrictions on use**

**Recommended Use** Polyester Primer Surfacer. For professional use only.

**Uses advised against** Uses other than recommended use.

**Details of the supplier of the safety data sheet**

**Manufacturer Address**

ITW Evercoat  
6600 Cornell Road  
Cincinnati, Ohio 45242  
Telephone: 513-489-7600

**May Also Be Distributed by:**

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**24-hour emergency phone number**

CHEMTREC: 1-800-424-9300  
INTERNATIONAL: 1-703-527-3887

**E-mail address:** Info@evercoat.com

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 2

**Label elements**

**Emergency Overview**

**Signal word**

**Danger**

Harmful if swallowed or if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor



**Appearance** Gray

**Physical state** Liquid

**Odor** Aromatic

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Wear eye/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use non-sparking tools
- Take precautionary measures against static discharge

**Precautionary Statements - Response**

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth
- In case of fire: Use CO2, dry chemical, or foam to extinguish.

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

- Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

May be harmful in contact with skin. Toxic to aquatic life with long lasting effects.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
Styrene	100-42-5	10 - 30
Talc (hydrous magnesium silicate)	14807-96-6	10 - 30

Man Made Glass Fiber	65997-17-3	5 - 10
Acetone	67-64-1	5 - 10
Magnesite	546-93-0	5 - 10
Toluene	108-88-3	1 - 5
Titanium Dioxide	13463-67-7	1 - 5
N,N-Dimethylaniline	121-69-7	0.1 - 1
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0.1 - 1
Mineral Spirits (Stoddard Solvent)	8052-41-3	0.1 - 1
Copper Naphthenate	1338-02-9	0.1 - 1
Crystalline Silica (Quartz)	14808-60-7	0.1 - 1

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Get medical advice/attention if you feel unwell.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Use dry chemical, Foam

##### Unsuitable extinguishing media

None

##### Specific hazards arising from the chemical

Flammable.

##### Explosion data

**Sensitivity to Mechanical Impact** None.  
**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Soak up with inert absorbent material.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Styrene 100-42-5	STEL: 20 ppm TWA: 10 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m <sup>3</sup> (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m <sup>3</sup> Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup>
Talc (hydrous magnesium silicate) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Man Made Glass Fiber 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable particulate matter	-	-
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

		The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	
Magnesite 546-93-0	-	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Titanium Dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
N,N-Dimethylaniline 121-69-7	STEL: 10 ppm TWA: 5 ppm S*	TWA: 5 ppm TWA: 25 mg/m <sup>3</sup> TWA: 19 mg/m <sup>3</sup> (vacated) TWA: 5 ppm Dimethyl aniline (vacated) TWA: 25 mg/m <sup>3</sup> Dimethyl aniline (vacated) TWA: 2 ppm (vacated) TWA: 8 mg/m <sup>3</sup> (vacated) STEL: 10 ppm Dimethyl aniline (vacated) STEL: 50 mg/m <sup>3</sup> Dimethyl aniline (vacated) S* Dimethyl aniline (vacated) S*	IDLH: 100 ppm TWA: 5 ppm TWA: 25 mg/m <sup>3</sup> STEL: 10 ppm STEL: 50 mg/m <sup>3</sup>
Mineral Spirits (Stoddard Solvent) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Copper Naphthenate 1338-02-9	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-	IDLH: 100 mg/m <sup>3</sup> Cu dust and mist TWA: 1 mg/m <sup>3</sup> Cu dust and mist
Crystalline Silica (Quartz) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls**

- Showers
- Eyewash stations
- Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin and body protection**

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**Physical state** Liquid  
**Appearance** Gray  
**Odor** Aromatic  
**Odor threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	56 °C / 133 °F	
Flash point	9 °C / 48 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

**Other Information**

**Softening point** No information available  
**Molecular weight** No information available  
**VOC content** Regulatory 1.9 lbs./gal. or 228 g/l. Actual 1.3 lbs./gal. or 156 g/l.  
    **Applied** 1.9 lbs/gal or 227 g/l.  
    **Packaged** 3.03 lbs/gal or 363 g/l.  
**Density** 11.35  
**Bulk density** No information available  
**SADT (self-accelerating decomposition temperature)** No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**  
 No information available

**Chemical stability**  
 Stable under normal conditions

**Possibility of Hazardous Reactions**  
 None under normal processing.

**Conditions to avoid**  
 Excessive heat.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	= 11.7 mg/L ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
N,N-Dimethylaniline 121-69-7	= 951 mg/kg ( Rat )	= 1770 mg/kg ( Rabbit )	> 0.5 - 5.0 mg/L ( Rat ) 4 h
Naphtha (petroleum), hydrotreated heavy 64742-48-9	> 6000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
Copper Naphthenate 1338-02-9	= 2 g/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5	A3	Group 2A	Reasonably Anticipated	X
Talc (hydrous magnesium silicate) 14807-96-6	-	Group 3	-	X
Man Made Glass Fiber 65997-17-3	-	Group 3	-	-
Toluene 108-88-3	-	Group 3	-	-
Titanium Dioxide 13463-67-7	-	Group 2B	-	X
N,N-Dimethylaniline 121-69-7	-	Group 3	-	-
Copper Naphthenate 1338-02-9	-	Group 2A	-	X
Crystalline Silica (Quartz) 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Not classifiable as a human carcinogen  
 Group 2A - Probably Carcinogenic to Humans  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present

**Chronic toxicity** May cause adverse liver effects. Contains a known or suspected reproductive toxin.  
**Target Organ Effects** Central nervous system, Central Vascular System (CVS), Eyes, Liver, Lungs, Reproductive System, Respiratory system, Skin, kidney.

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 1381 mg/kg  
**ATEmix (dermal)** 2954 mg/kg  
**ATEmix (inhalation-dust/mist)** 2.4 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
Styrene 100-42-5	2.95
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.7
N,N-Dimethylaniline 121-69-7	2.278

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent	-



			filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable
Copper Naphthenate 1338-02-9	Toxic

**14. TRANSPORT INFORMATION**

Note: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

**DOT**

UN/ID No UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II

**IATA**

UN/ID No UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II

**IMDG**

UN/ID No UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1
Toluene - 108-88-3	1.0
Naphthalene - 91-20-3	0.1
Ethyl Benzene - 100-41-4	0.1

**SARA 311/312 Hazard Categories**

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X
Toluene 108-88-3	1000 lb	X	X	X
Copper Naphthenate 1338-02-9	-	X	-	-

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
N,N-Dimethylaniline 121-69-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Styrene 100-42-5	Carcinogen
Toluene 108-88-3	Developmental
Titanium Dioxide	Carcinogen

13463-67-7	
Crystalline Silica (Quartz) 14808-60-7	Carcinogen
Naphthalene 91-20-3	Carcinogen
Ethyl Benzene 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X
Talc (hydrous magnesium silicate) 14807-96-6	X	X	X
Acetone 67-64-1	X	X	X
Magnesite 546-93-0	X	X	-
Toluene 108-88-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Butyl Alcohol 78-92-2	X	X	X
Crystalline Silica (Quartz) 14808-60-7	X	X	X
Ethanol, 2-(2-butoxyethoxy)- 112-34-5	X	-	X
Naphthalene 91-20-3	X	X	X
Ethyl Benzene 100-41-4	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

B2 - Flammable liquid, D2A - Very toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	-
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 03-Mar-2021

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**