

# PRODUCT FEATURES & APPLICATION



Touch Dry 10-40 min

# Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

## PREMIUM “OEM APPROVED” SURE SEAL SEAM & JOINT SEALERS

Stock CSW (White) Part 9002, CSB (Black) Part 9003,  
Stock CSC (Clear) Part 9001, CSG (Grey) Part 9004  
300 ml (11 oz) Cartridge's

### **Description:**

Dominion Sure Seal Sealants are one part, low cost high performance Hi Solid sealants. The cured sealant exhibits very good physical properties including excellent adhesion to a variety surfaces including painted and non painted metal, rubber, glass, wood, concrete. Dominion Sure Seal Sealers are also non staining. They possesses rubber-like characteristics and can be compressed or extended. Used for all sealing and adhesive applications. Dominion Sure Seal Sealers are of a non sag consistency for application with a standard caulking gun in vertical and horizontal joints.

### **Features:**

- High rubber content
- Cures to a tough rubber.
- Highly elastic with very little shrinkage.
- Low and high temperature flexibility.
- Fast drying
- Non sagging
- Paintable in 30 - 40 minutes.
- Serviceable temperatures from -20°f to 160°f
- Water resistant

### **Physical Properties:**

COLOUR: White, Black, Clear, Grey  
CONSISTENCY: Non Sag  
SOLIDS: 75%-95%  
TENSILE STRENGTH: 800 psi  
ELONGATION: Excess of 300%  
MODULUS:100: 140 psi  
WEIGHT PER GALLON: 1 pound

### **Application Instructions:**

- Cut cartridge nozzle to desired bead size and caulk.
- Use for channel glazing, Porcelain panel construction, Sealing and bedding applications subject to racking and distortions on automobiles, trucks, trailers, buses, boats and trailer bodies.
- Tent patching
- Bathtub caulk.  
Quarry tile and masonry joints, decks etc.

### **Surface Preparation:**

Surface should be clean and grease and oil free.

Touch Dry and Paintable in 10 – 40 min

Full Cure 24 plus hours

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

Call 1-800-265-0790 or visit us on the web [www.dominionsureseal.com](http://www.dominionsureseal.com)