SAFETY DATA SHEET.

Issuing date 08-May-2017

Revision Date 08-May-2017

Version 2.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

T Todaot laolitilloi	
Product name Product number	TEX COAT CHIPGUARD CLEAR 4323
<u>Product Type</u> Synonyms	Extremely Flammable Aerosol None
<u>Supplier's details</u> Recommended Use Uses advised against	Chip Guard. For Professional and Industrial Use Only. Not for sale to the general public.
Manufacturer/Supplier: Transtar Autobody Technologies 2040 Heiserman Drive Brighton, MI 48116 800-824-2843	
Emorgonov tolonhono numbor	

Emergency telephone number Chemical Emergency Phone Number


CHEMTREC: +1-703-527-3887 (INTERNATIONAL) 1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements



Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood Obtain special instructions before use Wear protective gloves/eye protection/face protection/protective clothing Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces.-No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water. Specific treatment(see First Aid on this label) If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse. IF INHALED : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell

4323 Tex Coat Chipguard Clear

Precautionary Statements - Storage Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

Less than 1% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
METHYL N-AMYL KETONE	110-43-0	20-30
ACETONE	67-64-1	20-30
DIMETHYLETHER	115-10-6	10-20
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	1-10
2-BUTOXYETHANOL	111-76-2	1-10
BUTYL BENZYL PHTHALATE	85-68-7	0.1-1
SOLVENT NAPHTHA	64742-94-5	0.1-1
XYLENE	1330-20-7	0.1-1
TOLUENE	108-88-3	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.		
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur. If symptoms persist, call a physician.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breahing, give artificial respiration. Get medical attention immediately. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.		
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.		
Most important symptoms/effects, a	acute and delayed		
Main Symptoms	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May damage fertility or the unborn child. May cause drowsiness or dizziness.		
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	Treat symptomatically.		

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Keep away from sources of ignition - No smoking. Cool containers / tanks with water spray.

Specific hazards arising from the chemical

Extremely Flammable/Flammable. Keep product and empty container away from heat and sources of ignition. No smoking. Cool containers/tanks with water spray. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation. Keep container away from heat, flames and all other sources of ignition. Keep container away from heat, flames, and all other sources of ignition. Keep away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.	
Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors can accumulate in low areas.	
Methods and materials for containr	nent and cleaning up	
Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Stop leak if you can do it without risk.	
Methods for cleaning up	Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Wear all appropriate Personal Protective Equipment (PPE). wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e. 40 to 95 F.(4 to 35 C). Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on hot surfaces. Take precautionary measures against static discharges. Avoid inhaling vapors or mists. May cause respiratory irritation if inhaled. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on hot surfaces. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.
Incompatible products	Store away from strong acids, alkalis, oxidizing agents.
Aerosol Level	2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL N-AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
DIMETHYLETHER 115-10-6	STEL: 500 PPM TWA: 400PPM	TWX: 400 PPM TWA: 1200 mg/m ³	IDLH: 1900 PPM (10 % LEL)
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields.	
Skin and body protection	Chemical resistant apron. Protective gloves.	
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.	
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Appearance Color	Aerosol Clear Colorless	Odor Odor Threshold	Solvent
<u>Property</u> pH Melting/freezing point Boiling point/boiling range	<u>Values</u> No information available No information available	<u>Remarks • Methods</u>	
Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit	-96.4 °C / -141 °F No information available No information available	Based on propellant	
lower flammability limit Vapor pressure Vapor density Specific Gravity Water solubility Partition coefficient: n-octanol/wate	0.823 Negligible		
Autoignition temperature Decomposition temperature Viscosity Explosive properties	No information available	Not applicable	
Other information			
VOC Content(%) MIR Value MIR Coating Category	0.38 1.39 ABT - Auto-body Trim MIR limit 1.70		

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Harmful if inhaled. May cause respiratory irritation. May cause drowsiness	or dizziness.
--	---------------

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation.

Ingestion May be harmful if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL N-AMYL KETONE 110-43-0	= 1600 mg/kg(Rat)	= 12.6 mL/kg (Rabbit)	> 2000 ppm (Rat)4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
DIMETHYLETHER 115-10-6	-	-	= 308.5 mg/L (Rat)4 h
PROPANE/ISOBUTANE/N-BUTAN E 68476-86-8	-	-	=31mg/L (Rat) 4 hr
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat)4 h
BUTYL BENZYL PHTHALATE 85-68-7	= 2330 mg/kg (Rat)	= 6700 mg/kg (Rat)	> 6.7 mg/L (Rat)4 h
SOLVENT NAPHTHA 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³(Rat)4 h
XYLENE 1330-20-7	= 3500 mg/kg(Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May damage fertility or the unborn child. May cause drowsiness or dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation	Causes skin irritation. Causes serious eye irritation.				
Sensitization	None known.	None known.			
Germ Cell Mutagenicity	Not a germ c	Not a germ cell mutagen.			
Carcinogenicity	The table bel	The table below indicates whether each agency has evaluated a listed ingredient as a			
	carcinogen.				
Chemical Name	ACGIH	IARC	NTP	OSHA	

2-BUTOXYETHANOL 111-76-2	-	Group 3	-	-
BUTYL BENZYL PHTHALATE 85-68-7	-	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
TOLUENE 108-88-3	-	Group 3	-	-

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity

This product does contain a chemical which is a known or suspected reproductive hazard. May damage fertility to or the unborn child.

Specific target organ systemic toxicity (single exposure) Specific target organ systemic toxicity (repeated exposure) Chronic toxicity	None under normal use conditions. None under normal use conditions. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be harmful if swallowed and enters airways.
Numerical measures of toxicity - P	roduct Information
Unknown Acute Toxicity The following values are calculated	Less than 1% of the mixture consists of ingredient(s) of unknown toxicity. I based on chapter 3.1 of the GHS document

Olikilowii Acute Toxicity	Less than 170 of the mixture consists of ingreaterit(s) of anniown toxicity.						
The following values are calculated	The following values are calculated based on chapter 3.1 of the GHS document 🗉						
ATEmix (oral)	4563 mg/kg						
ATEmix (dermal)	25513 mg/kg						
ATEmix (inhalation-gas)	177404 mg/l						
ATEmix (inhalation-dust/mist)	4.9 mg/l						
ATEmix (inhalation-vapor)	6894 mg/l						

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to fish Toxicity to microorganisms	
METHYL N-AMYL KETONE 110-43-0	-	126 - 137 mg/L LC50 Pimephales promelas 96h flow-through	-	-
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h

4323 Tex Coat Chipguard Clear

BUTYL BENZYL	0.02 - 0.25 mg/L EC50	1.0 - 10.0 mg/L LC50	-	0.9 - 1.1 mg/L EC50
PHTHALATE	Pseudokirchneriella	Oncorhynchus mykiss 96h		Daphnia magna 48h Static
85-68-7	subcapitata 96h 0.2 - 28.2	static 0.82 mg/L LC50		0.76 mg/L EC50 Daphnia
	mg/L EC50	Oncorhynchus mykiss 96h		magna 48h Flow through
	Pseudokirchneriella	flow-through 1.39 - 3.88		1.28 mg/L EC50 Daphnia
	subcapitata 72h	mg/L LC50 Pimephales		magna 48h semi-static 0.97
	Subcapitata 7211	promelas 96h flow-through		
				mg/L EC50 Daphnia magna
		0.78 mg/L LC50 Pimephales		48h
		promelas 96h static 1.0 -		
		10.0 mg/L LC50 Lepomis		
		macrochirus 96h static		
SOLVENT NAPHTHA	-	19 mg/L LC50 Pimephales	-	0.95 mg/L EC50 Daphnia
64742-94-5		promelas 96h static 2.34		magna 48h
04142 04 0		mg/L LC50 Oncorhynchus		magna 401
		mykiss 96h 1740 mg/L LC50		
		Lepomis macrochirus 96h		
		static 45 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 41 mg/L LC50		
		Pimephales promelas 96h		
XYLENE	_	13.4 mg/L LC50 Pimephales	-	3.82 mg/L EC50 water flea
1330-20-7		promelas 96h flow-through		48h 0.6 mg/L LC50
1550-20-7				Gammarus lacustris 48h
		2.661 - 4.093 mg/L LC50		Gammarus lacustris 401
		Oncorhynchus mykiss 96h		
		static 13.5 - 17.3 mg/L LC50		
		Oncorhynchus mykiss 96h		
		13.1 - 16.5 mg/L LC50		
		Lepomis macrochirus 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		7.711 - 9.591 mg/L LC50		
		Lepomis macrochirus 96h		
		static 23.53 - 29.97 mg/L		
		LC50 Pimephales promelas		
		96h static 780 mg/L LC50		
		Cyprinus carpio 96h		
		semi-static 780 mg/L LC50		
		Cyprinus carpio 96h 30.26 -		
		40.75 mg/L LC50 Poecilia		
		reticulata 96h static		
TOLUENE	433 mg/L EC50	15.22 - 19.05 mg/L LC50		5.46 - 9.83 mg/L EC50
108-88-3	Pseudokirchneriella	Pimephales promelas 96h	-	Daphnia magna 48h Static
100-00-3				11 5 mg/L EC50 Donkala
	subcapitata 96h 12.5 mg/L	flow-through 12.6 mg/L LC50		11.5 mg/L EC50 Daphnia
	EC50 Pseudokirchneriella	Pimephales promelas 96h		magna 48h
	subcapitata 72h static	static 5.89 - 7.81 mg/L LC50		
		Oncorhynchus mykiss 96h		
		flow-through 14.1 - 17.16		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 5.8 mg/L		
		LC50 Oncorhynchus mykiss		
		96h semi-static 11.0 - 15.0		
		mg/L LC50 Lepomis		
		macrochirus 96h static 54		
		mg/L LC50 Oryzias latipes		
		96h static 28.2 mg/L LC50		
		Poecilia reticulata 96h		
		semi-static 50.87 - 70.34		
		mg/L LC50 Poecilia		
		reticulata 96h static		
			L	

Persistence and degradability

Bioaccumulation

.

.

Chemical Name	log Pow
METHYL N-AMYL KETONE	1.98
110-43-0	

4323 Tex Coat Chipguard Clear

ACETONE	-0.24
67-64-1	
DIMETHYLETHER	-0.18
115-10-6	
PROPANE/ISOBUTANE/N-BUTANE	<=2.8
68476-86-8	
2-BUTOXYETHANOL	0.81
111-76-2	
BUTYL BENZYL PHTHALATE	3.57 - 4.91
85-68-7	
SOLVENT NAPHTHA	2.9 - 6.1
64742-94-5	
XYLENE	2.77 - 3.15
1330-20-7	
TOLUENE	2.7
108-88-3	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment	
Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.
Contaminated packaging	Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground	CONSUMER COMMODITY ORM-D
	or LIMITED QUANTITY
	•••

ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.
IMDG	UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
METHYL N-AMYL KETONE	Х	X	Х	Х	Х	Х	X	Х
ACETONE	Х	Х	Х	Х	Х	Х	Х	Х
DIMETHYLETHER	Х	Х	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	х	Х	Х	Х	Х
2-BUTOXYETHANOL	Х	Х	Х	Х	Х	Х	Х	Х
BUTYL BENZYL PHTHALATE	Х	Х	Х	Х	Х	Х	Х	Х

SOLVENT NAPHTHA	Х	Х	Х	Х	Х	Х	Х	Х
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х
TOLUENE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1.76862	1.0

SARA 311/312 Hazard Categories

INA ST 1/STZ Hazard Oategones	
Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BUTYL BENZYL PHTHALATE 85-68-7		X	X	
XYLENE 1330-20-7	100 lb			Х
TOLUENE 108-88-3	1000 lb	X	Х	X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
BUTYL BENZYL PHTHALATE 85-68-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
BUTYL BENZYL PHTHALATE - 85-68-7	Developmental
TOLUENE - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL N-AMYL KETONE 110-43-0	Х	X	Х
ACETONE 67-64-1	Х	X	Х
DIMETHYLETHER 115-10-6	Х	X	Х
2-BUTOXYETHANOL 111-76-2	Х	Х	Х
BUTYL BENZYL PHTHALATE 85-68-7	Х	X	Х
XYLENE 1330-20-7	Х	X	Х
TOLUENE 108-88-3	Х	X	Х

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION				
NFPA_	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 0	Personal protection B
Prepared By	Transtar Autobody Technologies			

Issuing date	
Revision Date	08-May-2017
Revision Note	08-May-2017

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet