## **Material Safety Data Sheet**

WHMIS	Protective Clothing	TDG Road / Rail

Section I. Product Identification and Uses			
Product Name	Rust Inhibitor Aerosol -1054	CI#	Not available.
Synonyms	Rust Inhibitor (1054)	DSL	Not available.
Chemical Name	Not applicable.	CAS #	Not applicable.
Chemical Formula	Chemical mixture.	Code	1054
Chemical Family	Hydrocarbons.	Molecular Weight	Not applicable.
Supplier	Rust Check Corporation 6175 Danville Road, Mississauga, Ontario L5T 2H7 (905) 670-5411	Emergency Number	CANUTEC ( 24 HR ) (613)996-6666
Material Uses	Multi-purpose rust inhibitor and lubricant.		

## Section 2. Hazardous Ingredients

Section 2. nazardous ingredients				
Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>	
1) Petroleum Distillates, Light	8052-41-3	1-5	INHALE (LD50) ppm/kg: Acute: >1400 (Rat).	
2) Petroleum Distillates, Heavy	8008-20-6 64742-81-0	3-7	<b>ORAL (LD50)</b> mg/kg: Acute: >5000 (Rat).	
3) Petroleum Distillates, Heavy	64742-54-7 64742-52-5	3-7	Not available.	
4) Petroleum Distillates, Light	64742-53-6	3-7	Not available.	
5) Propane	74-98-6	5-15	Not available.	
6) Isobutane	75-28-5	5-10	GAS (LC50): Acute: 142500 ppm 4 hour(s) [Rat].	

Physical State and Appearance	Liquid (Aerosol Concentrate).	Odor	Characteristic.
pH (1% Soln/Water)	Aerosol Portion: Not applicable. Liquid Portion: Not available.	Taste	Not available.
Odor Threshold	Propane: 22,000 mg/m <sup>3</sup>	Color	Red.
Volatility	Not available.		
Evaporation Rate	Aerosol Portion: faster than butyl acetate;Immediate at temperatures above -35°C. Liquid Portion: slower than butyl acetate.		
Melting Point	Not available.		
Boiling Point	Aerosol Portion: -42.1 to -0.5°C. Liquid Portion: Not available.		
Density	0.850 - 0.875 @ 20°C (Water = 1).		
Vapor Density	Greater than1.0 (Air = 1.0)		
Vapor Pressure	The highest known value is 7 mm of Hg (@ 20°C) (Petroleum distillate).		
LogK <sub>ow</sub>	Not available.		
Ionicity (Surface Active Agent)	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		

Rust Inhibitor (10	054)		Page Number: 2
WHMIS	8	Protective Clothing	TDG Road / Rail
	$\overline{\mathbf{T}}$		
A B-5 D-	2B		CONSUMER COMMODITY.
Conditions of Instability	No additional remain	ark.	
<b>Dispersion Properties</b>	Not available.		
Solubility	Not available.		

Section 4. Fire	Section 4. Fire and Explosion Data		
The Product is:	Extremely Flammable Aerosol		
Auto-ignition Temperature	Not available.		
Products of Combustion	These products are carbon oxides (CO, CO2), sulfur and other irritating gases.		
Flash Points	Not available.		
Flammable Limits	Not available.		
Extinguishing Media	<ul> <li>SMALL FIRE: Use DRY chemicals, carbon dioxide or foam.</li> <li>LARGE FIRE: Use foam or water fog.</li> <li>Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid spreading burning liquid with water used to cool containers.</li> <li>Self-contained respiratory protection should be provided for firefighters.</li> </ul>		
Flammability	The flammability of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame-extension of this product is greater than 45 cm. FIRE CODE: Level 3 Aerosol (as per NFPA 30B). Do not use in the presence of open flame or spark. Do not place in hot water or near radiators, stoves or other sources of heat.		
Risks of Explosion	Risk of explosion of the product in presence of mechanical impact: Do not subject aerosol cans to impact. Risk of explosion of the product in the presence of static discharge: Aerosol spray may be sensitive to static discharge due to flammable concentrate and flammable propellant. Vapours of this product may form a flammable/explosive mixture with air in enclosed areas and come into contact with open flames, sparks or static discharge. Do NOT expose aerosol containers to open flames, heat or ignition sources. Container may explode if heated.		

## Section 5. Reactivity

Stability	The product is stable.	
Hazardous Decomposition Products	These products are carbon oxides (CO, CO2), sulfur and other irritating gases.	
Degradability	Not available.	
Products of Degradation	Not available. Not available.	
Corrosivity	No specific information is available in our database regarding the corrosivity of this product in presence of various materials.	
Reactivity	Avoid contact with strong oxidizing agents, strong acids and strong alkalies. Keep away from heat, sparks, open flame and all possible ignition sources.	
Instability Temperature	Not available.	
Conditions of Instability	No additional remark.	

Rust Inhibitor (1054)

Page Number: 3

WHMIS

Protective Clothing



CONSUMER COMMODITY.

TDG Road / Rail

Section 6. To	xicological Properties	
Routes of Entry	Ingestion. Inhalation. Skin contact. Eye contact.	
TLV	Petroleum distillate TWA: 300 (ppm) from ACGIH (TLV)	
	Propane Simple asphyxiant.	
	Consult local authorities for acceptable exposure limits.	
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): >8000 mg/kg [Rat]. (Petroleum distillate). Acute toxicity of the gas (LC50): 142500 ppm 4 hour(s) [Rat]. (Isobutane). Acute toxicity of the vapor (LC50): >5900 ppm 4 hour(s) [Rat]. (Petroleum distillate).	
Chronic Effects on Humans	Prolonged or repeated skin contact may lead to dermatitis.	
Acute Effects on Humans	EYE CONTACT: May cause redness. SKIN CONTACT: Prolonged or repeated contact may cause irritation. INHALATION: May cause chemical pneumonitis if sprayed and mist is inhaled into lungs. INGESTION: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Can be fatal if inhaled or ingested. This product may irritate eyes and skin upon contact.	
Synergetic Products (Toxicologically)	Not available.	
Irritation/Corrosivity	Not available.	
Sensitization	None known.	
Carcinogenic Effects	No ingredients listed as carcinogens by IARC OR ACGIH.	
Toxic Effects on Reproduction	DEVELOPMENTAL TOXICITY: Not available.	
Teratogenic Effects	TERATOGENIC EFFECTS: Not available.	
Mutagenic Effects	MUTAGENIC EFFECTS: Not available.	
Section 7. Pre	eventive Measures	
Small Spill and Leak	Ventilate area and eliminate all sources of ignition. Keep away from heat. Absorb with an inert DRY material and place in an appropriate waste disposal container.	
Personal Protective Equipment	Recommend Safety glasses, chemical resistant gloves and NIOSH Approved respirator for organic mists and vapours.	
Large Spill and Leak	Not applicable for aerosol containers.	
Protective Clothing	Not applicable for aerosol containers.	
Engineering Controls	Use under well-ventilated conditions.	
Precautions	Contents under pressure. Container may explode if heated. Direct inhalation of spray may be harmful. Keep out of reach of children.	
Storage	Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 50°C or in direct sunlight.	

Continued on Next Page

Rust Inhibitor (1054) Page Number: 4 WHMIS Protective Clothing TDG Road / Rail T  $\nabla X$ A B-5 D-2B CONSUMER COMMODITY. Handling Do not use in the presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapours or spray mists. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap and water. Recycle to process, if possible. Consult your local or regional authorities. Do not dispose in sewers. When container Waste Disposal is empty, press button to release all pressure, then dispose of in garbage can. **Special Shipping** Not available. Information

Section 8. First Aid		
Eye Contact	Flush eyes with plenty of running water for at least 15 minutes, lifting upper and lower lids, occasionally. Get medical attention.	
Skin Contact	Wash thoroughly with soap and water. If irritation persists, get medical attention. Remove contaminated clothing and wash before reuse.	
Hazardous Skin Contact	No additional information.	
Slight Inhalation	Remove affected person to fresh air. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Get medical attention.	
Hazardous Inhalation	No additional information.	
Slight Ingestion	If swallowed, call physician or poison control centre immediately. DO NOT induce vomiting. Rinse mouth with water. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis which can be fatal.	
Hazardous Ingestion	No additional information.	

Section 9	9. MSDS Preparation	
References	Not available.	
No additional r	emark.	
Validated by R	egulatory Affairs Dept. on March 31, 2016	
Emerg	ency Phone: (905) 670-5411 , (613)996-666	6,1-800-265-0790
Responsable Name/ Telephone No.		
Classific	ation	
TDG Road / Rail	CONSUMER COMMODITY.	
	Not applicable.	
WHMIS	WHMIS CLASS A: Compressed gas. WHMIS CLASS B-5: Flammable aerosol. WHMIS CLASS D-2B: Material causing other toxic effects (TOXIC).	
Continu	ed on Next Page	

Rust Inhibitor (1054)		Page Number: 5
WHMIS	Protective Clothing	TDG Road / Rail
A B-5 D-2B	-	CONSUMER COMMODITY.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.