

Technical Data Sheet

Transtar CP Basecoat Binder and CP Basecoat Balancer have been formulated as comparable offerings for the most common major manufacturer's products. Since these are similar products, they are intended for use in a comparable manner as the color formula indicates. Transtar products have been developed to provide similar physical properties of their competitors including viscosity, solids, weight per gallon, and basecoat compatibility.

SURFACE PREPARATION



Refer to topcoat manufacture for surface preparation.

MIXING & APPLICATION

CP Basecoat Binder 7232-1D, is comparable to Axalta* 62320F Basecoat Binder and CP Basecoat Balancer, 7233-1D, is comparable to Axalta* 62330F Basecoat Balancer, (Primarily used in ChromaPremier®). These products are intended for use in a similar manner as the Axalta product.

Agitate thoroughly before use. Refer to color manufacturer's formulas for required amounts. (Use the same amount of Transtar material as that indicated for the Axalta item that it replaces.) Always use accurate weights and measures.

*DISCLAIMER: ChromaBase® and ChromaPremier® Basecoat Colors are registered trademarks of Axalta Coating Systems. Axalta does not manufacture, endorse, or guarantee Transtar products.

PRODUCT SPECIFICATIONS

Color: Clear liquid	Shelf Life: 3 years
Size: 7232-1D, CP Basecoat Binder, Gallon 7233-1D CP Basecoat Balancer, Gallon	

REGULATORY

Category: Color Coating	7232-1D	Weight % of Exempt Compounds	0
VOC Actual	6.44#/gal (772 g/l)	Volume % of Exempt Compounds	0
VOC Regulatory	6.44#/gal (772 g/l)	Density of Material #/gal	7.53
Weight % of Volatiles	85.54		
Weight % of Water	0		
Category: Color Coating	7233-1D	Weight % of Exempt Compounds	0
VOC Actual	6.13#/gal (735 g/l)	Volume % of Exempt Compounds	0
VOC Regulatory	6.13#/gal (735 g/l)	Density of Material #/gal	7.69
Weight % of Volatiles	79.71		
Weight % of Water	0		

Recommendations:

- CP Basecoat Binder and CP Basecoat Balancer products MUST be sealed after each use to prevent moisture and contaminants from entering.
- To avoid applying kicked out basecoat, it is always good shop practice to spray a test panel.
- Always turn on intermix machine for agitation first thing in the morning to ensure toners and Transtar products are sufficiently agitated, which will help to avoid color mismatch issues.

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.