

Technical Data Sheet

Super Wet Look Acrylic Enamel Catalyst is designed for use in acrylic enamel color systems to improve flow and leveling for an improved finish. It will produce a hard, durable finish with excellent gloss and chemical resistance. Super Wet Look is designed to provide a higher level of gloss, with long-term gloss retention.

SURFACE PREPARATION



Refer to topcoat manufacture for surface preparation.

MIXING & APPLICATION

Reduce acrylic enamel per paint manufacturers instructions. Add Super Wet Look Acrylic Enamel Catalyst at a rate of 8 parts color to 1 part catalyst, as recommended by the paint manufacturer. Apply per paint manufacturers instructions. Clean equipment thoroughly after use. Note: Catalyzed enamels left in spray gun will harden. Keep activator closed tightly after use, since exposure to air will cause gelation.

PRODUCT SPECIFICATIONS

Color: Clear liquid	Shelf Life: 3 years
Size: 8105 - ¼ pint, 8108 - pint	% Solids: 73%

REGULATORY

Category: Single Stage Coating	8105, 8108	Weight % of Exempt Compounds	0
VOC Actual	2.38#/gal (285 g/l)	Volume % of Exempt Compounds	0
VOC Regulatory	2.38#/gal (285 g/l)	Density of Material #/gal	8.90
Weight % of Volatiles	26.71		
Weight % of Water	0		

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.