

Technical Data Sheet

Transtar’s Urethane Grade Reducers are designed to be used in Transtar’s primers, sealers, topcoats and clearcoats. Additionally, this product can be used in virtually all brands of urethane primers, sealers, topcoats, and clears. Transtar’s Urethane Grade Reducers are suitable for overall and spot/panel refinishing and assist in producing brilliant gloss and superior leveling. This reducer is completely alcohol free and is 99.96% water free.

MIXING/APPLICATION

Read all directions for safe and proper usage and application of this product. Refer to the specific label directions for the primer, sealer, topcoat or clearcoat in order to determine proper reduction ratios.

Note: This product must be blended with other materials before application. Review and understand the warnings on all containers since the sprayable mixture will have the hazards of its components.

PRODUCT SPECIFICATIONS/REGULATORY

Speed/Temperature: Fast - 60-70°F (16-21°C)		Speed/Temperature: Medium - 65-80°F (18-26°C)	
Sizes: 6701 (Gallon), 6704 (Quart), 6705 (5 Gallon)		Sizes: 6711 (Gallon), 6714 (Quart), 6715 (5 Gallon)	
Shelf Life	5 years	Shelf Life	5 years
VOC Actual	7.47#/gal (895 g/l)	VOC Actual	7.44#/gal (891 g/l)
VOC Regulatory	7.47#/gal (895 g/l)	VOC Regulatory	7.44#/gal (891 g/l)
Weight % of Volatiles	100%	Weight % of Volatiles	100%
Weight % of Water	0	Weight % of Water	0
Weight % of Exempt Compounds	0	Weight % of Exempt Compounds	0
Volume % of Exempt Compounds	0	Volume % of Exempt Compounds	0
Density of Material	7.47	Density of Material	7.44
Speed/Temperature: Slow - 75-90°F (24-32°C)		Speed/Temperature: Extra Slow - 90°F+ (32°C+)	
Sizes: 6721 (Gallon), 6724 (Quart), 6725 (5 Gallon)		Sizes: 6741 (Gallon)	
Shelf Life	5 years	Shelf Life	5 years
VOC Actual	7.46#/gal (894 g/l)	VOC Actual	7.65#/gal (916 g/l)
VOC Regulatory	7.46#/gal (894 g/l)	VOC Regulatory	7.65#/gal (916 g/l)
Weight % of Volatiles	100%	Weight % of Volatiles	100%
Weight % of Water	0	Weight % of Water	0
Weight % of Exempt Compounds	0	Weight % of Exempt Compounds	0
Volume % of Exempt Compounds	0	Volume % of Exempt Compounds	0
Density of Material	7.46	Density of Material	7.65
Speed/Temperature: Extreme Heat			
Sizes: 6751 (Gallon)			
VOC Actual	7.5#/gal (899 g/l)	Weight % of Exempt Compounds	0
VOC Regulatory	7.5#/gal (899 g/l)	Volume % of Exempt Compounds	0
Weight % of Volatiles	100%	Density of Material	7.5
Weight % of Water	0		

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.

Visit www.tat-co.com to assure you are using most updated TDS, to view in other languages and for links to Standard Operating Procedures (SOPs).

TRANSTAR AUTOBODY TECHNOLOGIES • 2040 HEISERMAN DRIVE, BRIGHTON, MI 48114 • (800) 824-2843

FAX (800) 477-7923 • EMAIL: info@tat-co.com