

PREMIUM COARSE CUT PASTE COMPOUND Suitable for gel coats and painted finishes



# Key Benefits

# • VersatileEngineered for both gel coats and painted finishes, removing up to<br/>P800 sanding marks and leaving a high gloss finish• High Quality AbrasiveNo haze, no die back• Water-BasedCleans up easily and extends pad life



Farécla Products Ltd | +44 (0) 1920 465 041 | enquiries@farecla.com | www.farecla.com

# Product Description

Premium Paste Compound is a medium aggressive, water-based cutting compound capable of removing up to P800 sanding marks as well as delivering a high gloss finish. With added lubrication, it is also resistant to drying out in hot conditions and on large surfaces. Often used as the sole compound on white gel coats, it can be applied in the first stage of a two part compounding process where higher gloss and lower swirl is required.

# **Product Information**

**Size** 3.5kg (123oz) Code PRP301 Ctn Qty 4

# **Profile Premium**

Coarse Cut Paste Compound




### Use With

#### **Machine Application**



G Mop 8" Twisted Wool Pad - Single Sided GMW801



G Mop Flexible Back Plate for 8" Pads GMB814 (14mm thread) GMB858 (5/8" thread) GMB816 (16mm thread)



G Mop 8" Twisted Wool Pad - Double Sided GMW806



Adaptor for G Mop 8" Double Sided Wool Pad GMA014 (14mm thread) GMA058 (5/8" thread) GMA016 (16mm thread)

# How To Use

#### **Machine Application**



Sand area - Profile Premium Paste Compound removes up to P1200



Attach G Mop 8" Single Sided Wool Pad to a polisher



Mix product well and apply small quantity of the product to the surface or pad



Spread and compound at 1500 - 1800rpm



Wipe clean with a Finishing Cloth

\*It is always recommended to test on an inconspicuous area prior to general use

# Technical Information

Appearance: White coloured paste Viscosity: High viscosity VOC Content: 0g/L Relative Density: 1.65 pH: 10 Surface Types: Marine gel coats, aerospace, wood, caravan & motorhome etc.

## Additional Information

Clean applicators before and after use with a Spurring Brush to prevent dried product damaging the surface being worked on.



Spurring Brush 1090005

