

Technical Data Sheet

Ultimate Finish System™ Swirl Remover easily removes fine swirl marks and leaves a high gloss finish with minimal effort. Swirl Remover improves color, clarity and shine, leaving a polished, showroom finish. Though safe on all paints, Swirl Remover is specially formulated for prime results on darker colors. For best results, use with Transtar’s Gold Foam Pad 5292.

MIXING



Mix Ratio: Ready to Use
Pot Life: N/A

SURFACE PREPARATION



Wipe surface clean with a clean, dry, non-abrasive cloth.

APPLICATION



Do not apply in direct sunlight. Shake container well before use. Apply a 1.25” wide by 6” long ribbon (for every 2’ x 2’ area) of Swirl Remover. For best results, use sparingly. Spread with pad to minimize sling. Using a buffer at low speed (1000-1200 rpm), work material in a circular overlapping motion with Swirl Remover Gold Foam Pad 5292 while applying uniform pressure. As shine appears, reduce buffer pressure. Continue buffing to desired gloss. Finish by removing any residue with clean microfiber cloth.

PRODUCT SPECIFICATIONS

Color: White	Shelf Life: 3 years
Size: Quart (5384)	

REGULATORY

VOC Content: <13% by weight	Category: Automotive Rubbing or Polishing Compound
-----------------------------	----------------------------------------------------

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.