

Technical Data Sheet

Ultimate Finish System™ Tri-Cut II is designed to offer one product for three uses: 1) as a compound 2) as a swirl remover and 3) as a polisher. Tri-Cut II is safe for use on all paints.

MIXING



Mix Ratio: Ready to Use
 Pot Life: N/A

SURFACE PREPARATION



Wash surface to be sanded with soap and water.
 Sand 1200-2000 grit, wet or dry until imperfections or defects are removed. Finish sand with 1500-2000 grit.

APPLICATION



Ultimate Finish System™ Tri-Cut II is designed to offer 1 product for three uses.

- Remove grade 1200 grit and finer sand scratches with a wool compounding pad 5200/5260 or Cutting Compound Orange Foam Pad 5272 and an air or electric buffer (1500-2000 RPM.)
- For 1500 and finer imperfections use a Machine Polish White Foam Pad at 1200-1500 RPM
- Finish to desired gloss with a Swirl Remover Gold Foam Pad 5292 at 1000-1200 RPMs. Safe for use on all paints.

Do not apply in direct sunlight. Shake container well before use. Apply with an air or electric buffer, at speeds recommended above using the recommended pads to achieve best results. Apply enough of Tri-Cut II to the painted surface working in a 2 ft x 2 ft or panel size area. To minimize sling, spread with the compounding/polish pad before starting machine. Start machine and buff using light to medium pressure to achieve desired results. Reduce pressure as material begins to dry. Spur compound pads as necessary to assist with clean up. Finishing can be accomplished by hand or by buffer and Machine Polish White Foam Pad 5282. Apply a small amount of material, and allow material to haze over. Buff or polish to a high gloss shine. If machine applied, keep buffer moving to prevent rubbing through topcoat. After desired gloss is obtained, wash surface with soap and water and dry with a soft cloth to avoid scratching the surface.

Note: If material slings onto an adjacent panel or plastic part, remove spatter with a damp cloth as soon as possible.

Avoid contact with convertible tops, vinyl tops and plastic windows on convertibles.

Note: If using a new dry pad, mist the pad with water until moist.

Note: Misting the surface with water while working with Tri-Cut II will produce a higher gloss.

PRODUCT SPECIFICATIONS

Color: White	Shelf Life: 3 years
Size: Gallon (5331), Quart (5334)	

REGULATORY

VOC Content: <17% by weight	Category: Automotive Rubbing or Polishing Compound
-----------------------------	--

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.