



DESCRIPTION:

Presta Marine Chroma Swirl Remover™ is designed to remove swirls from Gel Coat and both fresh and cured painted surfaces, while leaving a brilliant high-gloss finish. If the swirls are heavy and/or cured, the best results are achieved by compounding, polishing and then using Chroma Swirl Remover.

DIRECTIONS:

Shake well before using. Apply a 1" (25 mm) dab of Chroma Swirl Remover to a 2'x 2' (.6m x .6m) section and spread with the polish pad. Buff at slower speeds (1200 to 1800 rpm). Buff until the product is mostly gone. Wipe surface with a Presta Micro Fiber Cloth (# 800135).

FEATURES & BENEFITS

Emulsion formula	<ul style="list-style-type: none"> Removes swirls from fresh and cured paint surfaces Produces a clean, high-gloss finish that doesn't wash away
Water-based product	<ul style="list-style-type: none"> Cuts fast Finishes clean Easy to use and cleans up quickly
VOC Compliant profile	<ul style="list-style-type: none"> Contains no fillers, waxes or silicones

RECOMMENDED PAD:

For best results, use with Presta blue foam pad #890145 or blue wool pad (#890144 – single sided, #890164 – double sided).

PACKAGE SIZES:

- 32 fl. oz. 133632
- 1 gallon 133601



PRESTA® MARINE PRODUCTS
KEEPING YOUR WATERCRAFT CLEAN & PROTECTED

**CHROMA SWIRL
REMOVER™**

PRODUCT FAQ'S:

Q1: Is Chroma Swirl Remover body shop safe?

A1: Chroma Swirl Remover is body shop safe and contains not silicone, wax, or fillers.

Q2: Will Chroma Swirl Remover work on other materials other than gel coat?

A2: Yes, Chroma Swirl Remover will provide a high gloss finish on automotive clear coats and single stage finishes.

Q3: Can Chroma Swirl Remover be used with other Presta buffing systems?

A3: Yes, Chroma Swirl Remover is compatible with all Presta buffing products and systems.

Q4: How do I know what Presta pad to use with Chroma Swirl Remover?

A4: Presta products have a color coded banner behind the Presta logo on each bottle that matches the color of the buffing pad that should be chosen for use. The blue foam pad (#890145) should be used.